



Dimmable LED BR30

Ordering Information

Stock Code	Item name	Lumens ² (lm)	Watts (w)	CCT ¹ (k)	Efficacy (lm/w)	CRI	Beam Angle	Lifetime ³ (h)	Base type	Voltage (v)	Certification	Equivalent ⁴ (w)
PLT-10602	BR30	650	8	4000	81	80	-	25,000	E26	120	UL, CUL	65



3 THREE YEARS WARRANTY

Compatible Dimmer List:**

AH SDM/600/WHTTE
ALMOND LUXDM600-12
CTL DM600-12-3
GE 18024
LEVITON 603-6631-A
LEVITON 6631-A
LEVITON 6631-LA
LEVITON NO.6672
LEVITON NO.IPL06
LUTRON DV-600PH-WH
LUTRON DV-603P
LUTRON DV-603PH-WH
LUTRON DVW-600PH-WH
LUTRON S-603PH-WH
LUTRON TG-600PH-WH

Dimensions

Model	M.O.L.	Diameter
BR30	5.08"	3.74"

Note: Lamp shape conforms to ANSI C78.21-2003.
Note: Designed to comply with RoHS Directive 2002/95/EC.

Energy Savings

Model Number	Equivalent*	Energy Savings
L4-BR30D-8W-40	65W Incandescent	\$157

1. CCT Range complies to ANSI C78.377-2008.
2. Thermally stable typical lumens (± 10%)
3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.
4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.
Note: All lamps meet Energy Star® Integral LED Lamp requirements, and will be submitted for testing.
Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh.
Does not include maintenance and replacement lamp savings.

*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.
**Tested to a maximum of 18 lamps per dimmer with proper functioning.