



## Dimmable LED BR30



**3** THREE YEARS WARRANTY

### Ordering Information

Stock Code	Item name	Lumens <sup>2</sup> (lm)	Watts (w)	CCT <sup>1</sup> (k)	Efficacy (lm/w)	CRI	Beam Angle	Lifetime <sup>3</sup> (h)	Base type	Voltage (v)	Certification	Equivalent <sup>4</sup> (w)
PLT-10603	BR30	650	8	5000	81	80	-	25,000	E26	120	UL, CUL	65

### Compatible Dimmer List:\*\*

AH SDM/600/WHTTE  
 ALMOND LUXDM600-12  
 CTL DM600-12-3  
 GE 18024  
 LEVITON 603-6631-A  
 LEVITON 6631-A  
 LEVITON 6631-LA  
 LEVITON NO.6672  
 LEVITON NO.IPL06  
 LUTRON DV-600PH-WH  
 LUTRON DV-603P  
 LUTRON DV-603PH-WH  
 LUTRON DVW-600PH-WH  
 LUTRON S-603PH-WH  
 LUTRON TG-600PH-WH

### Dimensions

Model	M.O.L.	Diameter
BR30	5.08"	3.74"

Note: Lamp shape conforms to ANSI C78.21-2003.  
 Note: Designed to comply with RoHS Directive 2002/95/EC.

### Energy Savings

Model Number	Equivalent*	Energy Savings
L4-BR30D-8W-50	65W Incandescent	\$157

1. CCT Range complies to ANSI C78.377-2008.
2. Thermally stable typical lumens ( $\pm 10\%$ )
3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.
4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.

Note: All lamps meet Energy Star® Integral LED Lamp requirements, and will be submitted for testing.

Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh.

Does not include maintenance and replacement lamp savings.

\*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

\*\*Tested to a maximum of 18 lamps per dimmer with proper functioning.