





## **Dimmable LED PAR20**







Ordering Information

Stock Code	Item name	Lumens <sup>2</sup>	Watts	CCT <sup>1</sup>	Efficacy	CRI	Beam Angle	Lifetime <sup>3</sup>	Base type	Voltage	Certification	Equivalent <sup>4</sup>
Stock Gode	itemmanie	(lm)	(w)	(k)	(lm/w)	CKI	Dealli Aligie	(h)	Dase type	(v)	Certification	(w)
PLT-10604	PAR20	500	7	2700	71	80	40°	25,000	E26	120	UL, CUL	50

## Compatible Dimmer List:\*\*

AH SDM3/1000/WHTTE LUTRON D-600R-WH ALMOND LUXDM600-12 LUTRON DV-600PH-WH CTL DM600-12-3 LUTRON DV-603P GE 18024 LUTRON DV-603PH-WH LEVITON 603-6631-A **LUTRON DV-603PR** LEVITON 6631-A LUTRON S-600-AL LEVITON 6631-LA LUTRON S-600-IV LEVITON NO.6672 LUTRON S-600PR-WH LEVITON IPI06-1LZ LUTRON S-603PH-WH LEVITON S-600P-WH LUTRON TG-600PH-WH

## **Dimensions**

Model	M.O.L.	Diameter
PAR20	3.19"	2.48"

Note: Lamp shape conforms to ANSI C78.21-2003.

Note: Designed to comply with RoHS Directive 2002/95/EC.

## **Energy Savings**

Model Number	Equivalent*	Energy Savings			
L4-PAR20D-7W-27-40	50W Halogen	\$118			

- 1. CCT Range complies to ANSI C78.377-2008.
- 2. Thermally stable typical lumens (± 10%)
- $3. \ \ \, \text{Rated life is based on 70\% lumen maintenance, and engineering testing and probability analysis.}$
- 4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.

Note: All lamps meet Energy Star® Integral LED Lamp requirements, and will be submitted for testing.

Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh.

Does not include maintenance and replacement lamp savings.

\*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

<sup>\*\*</sup>Tested to a maximum of 18 lamps per dimmer with proper functioning.