

## **Dimmable LED PAR38**









Ordering Information

Stock Code	Item name	Lumens <sup>2</sup> (Im)	Watts (w)	CCT <sup>1</sup> (k)	Efficacy (lm/w)	CRI	Beam Angle	Lifetime <sup>3</sup> (h)	Base type	Voltage (v)	Certification	Equivalent <sup>4</sup> (w)
PLT-10606	PAR38	1250	15	2700	83	80	40°	25,000	E26	120	UL, CUL	100

## Compatible Dimmer List:\*\*

AH SDM/600/WHTTE AH SDM3/1000/WHTTE CTL DM600-12-3 LEVITON 603-6631-A LEVITON 6631-A LEVITON 6631-LA

LEVITON S-600P-WH LUTRON D-600R-IV

LUTRON D-600R-WH

LUTRON D-600RH-DK

...-----

LUTRON DV-603P

LUTRON DV-603PH-WH LUTRON S-600

LUTRON S-600-AL

LUTRON S-600H-WH

LUTRON S-603PH-WH

LUTRON S-603PH-WH

CCT Range complies to ANSI C78.377-2008.

2. Thermally stable typical lumens ( $\pm$  10%)

 $3. \ \ \text{Rated life is based on } 70\% \ \text{lumen maintenance, and engineering testing and probability analysis.}$ 

4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.

Note: All lamps meet Energy Star® Integral LED Lamp requirements, and will be submitted for testing. Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh.

Does not include maintenance and replacement lamp savings.

\*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

## Dimensions

Model	M.O.L.	Diameter
PAR38	5.16"	4.72"

Note: Lamp shape conforms to ANSI C78.21-2003.

Note: Designed to comply with RoHS Directive 2002/95/EC.

## **Energy Savings**

Model Number	Equivalent*	Energy Savings		
L4-PAR38D-15W-27-40	120W Halogen	\$289		

<sup>\*\*</sup>Tested to a maximum of 10 lamps per dimmer with proper functioning.