



Dimmable LED PAR38



Ordering Information

Stock Code	Item name	Lumens <sup>2</sup> (lm)	Watts (w)	CCT <sup>1</sup> (k)	Efficacy (lm/w)	CRI	Beam Angle	Lifetime <sup>3</sup> (h)	Base type	Voltage (v)	Certification	Equivalent <sup>4</sup> (w)
PLT-10607	PAR38	1050	15	2700	70	90	40°	25,000	E26	120	UL, CUL	100

Compatible Dimmer List:\*\*

- AH SDM/600/WHTTE
- AH SDM3/1000/WHTTE
- CTL DM600-12-3
- LEVITON 603-6631-A
- LEVITON 6631-A
- LEVITON 6631-LA
- LEVITON S-600P-WH
- LUTRON D-600R-IV
- LUTRON D-600R-WH
- LUTRON D-600RH-DK
- LUTRON DV-603P
- LUTRON DV-603PH-WH
- LUTRON S-600
- LUTRON S-600-AL
- LUTRON S-600H-WH
- LUTRON S-603PH-WH
- LUTRON TG-600PH-IV

Dimensions

Model	M.O.L.	Diameter
PAR38	5.16"	4.72"

Note: Lamp shape conforms to ANSI C78.21-2003.  
Note: Designed to comply with RoHS Directive 2002/95/EC.

Energy Savings

Model Number	Equivalent*	Energy Savings
L4-PAR38DG-15W-27-40	100W Halogen	\$234

1. CCT Range complies to ANSI C78.377-2008.  
2. Thermally stable typical lumens (± 10%)  
3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.  
4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.  
Note: All lamps meet Energy Star® Integral LED Lamp requirements, and will be submitted for testing.  
Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh.  
Does not include maintenance and replacement lamp savings.

\*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.  
\*\*Tested to a maximum of 10 lamps per dimmer with proper functioning.