



**Dimmable LED MR16**



**3 THREE YEARS WARRANTY**

**Ordering Information**

Stock Code	Item name	Lumens <sup>2</sup> (lm)	Watts (w)	CCT <sup>1</sup> (k)	Efficacy (lm/w)	CRI	Beam Angle	Lifetime <sup>3</sup> (h)	Base type	Voltage (v)	Certification	Equivalent <sup>4</sup> (w)
PLT-10611	MR16	500	7	3000	71	80	40°	25,000	GU10	120	UL, CUL	50

**Compatible Dimmer List:\*\***

- ALMOND LUXDM600-12
- LEVITON 6631-LA
- LEVITON 6684
- LUTRON CT-103P-WH
- LUTRON D-600PH-DK
- LUTRON DV-603P600W
- LUTRON DV-603PR
- LUTRON S-600
- LUTRON S-600PR-WH
- LUTRON TGCL-153PH-WH
- LUTRON TGCL-153PLH-WH
- TOP HCL453PTC
- TOP HCL453PW

**Dimensions**

Model	M.O.L.	Diameter
MR16	2.13"	1.97"

Note: Lamp shape conforms to ANSI C78.21-2003.  
 Note: Designed to comply with RoHS Directive 2002/95/EC.

**Energy Savings**

Model Number	Equivalent*	Energy Savings
L4-MR16GU10D-7W-30-40	50W Halogen	\$118

1. CCT Range complies to ANSI C78.377-2008.
2. Thermally stable typical lumens (± 10%)
3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.
4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.  
 Note: All lamps meet Energy Star® Integral LED Lamp requirements, and will be submitted for testing.  
 Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh.  
 Does not include maintenance and replacement lamp savings.

\*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.  
 \*\*Tested to a maximum of 10 lamps per dimmer with proper functioning.