



## Dimmable LED Candle



**3 THREE YEARS WARRANTY**

### Ordering Information

Stock Code	Item name	Lumens <sup>2</sup> (lm)	Watts (w)	CCT <sup>1</sup> (k)	Efficacy (lm/w)	CRI	Lifetime <sup>3</sup> (h)	Base type	Voltage (v)	Certification	Equivalent <sup>4</sup> (w)
PLT-10615	Candle	325	5	3000	65	80	25,000	E12	120	UL, CUL, Energy Star	40

### Compatible Dimmer List:\*\*

ALMOND LUXDM600-12  
 LEVITON 6631-LA  
 LEVITON 6684  
 LUTRON CT-103P-WH  
 LUTRON D-600PH-DK  
 LUTRON DV-603P600W  
 LUTRON DV-603PR  
 LUTRON S-600  
 LUTRON S-600PR-WH  
 LUTRON TGCL-153PLH-WH  
 TOP HCL453PTC  
 TOP HCL453PW

### Dimensions

Model	M.O.L.	Diameter
Candle	3.83"	1.38"

Note: Lamp shape conforms to ANSI C78.21-2003.

Note: Designed to comply with RoHS Directive 2002/95/EC.

### Energy Savings

Model Number	Equivalent*	Energy Savings
L2-CandleD-5W-30-E12(Clear)	40W Incandescent	\$96

1. CCT Range complies to ANSI C78.377-2008.

2. Thermally stable typical lumens (± 10%)

3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.

4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.

Note: All lamps meet Energy Star® Integral LED Lamp requirements, and will be submitted for testing.

Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh.

Does not include maintenance and replacement lamp savings.

\*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

\*\*Tested to a maximum of 10 lamps per dimmer with proper functioning.