

# 55136

## LED 96" DESIGNER STRIP

### TECHNICAL DATA SHEET

#### FEATURES



#### DIRECT LINEAR AMBIENT LUMINAIRES LOW-BAY LUMINAIRES FOR COMMERCIAL AND INDUSTRIAL BUILDINGS

- Provides smooth uniform light.
- Low-profile which meets limitless range of applications.
- Use 30% less energy than a linear fluorescent fixtures

#### HOUSING

- Die formed 24 gauge cold rolled steel.
- All steel surfaces are painted after fabrication with high gloss baked white matte powder paint.
- Diffusing lens for soft even light

#### MOUNTING

Designed for surface, pendant or stem mounted.

#### DIMMING

- 0-10V dimming function, dimming range is 10% - 100%

#### APPLICATION


Larger warehouses, retail applications, commercial buildings and work areas.

#### SPECIFICATIONS

Power Consumption	40W
Input Voltage	120-277V
Power Factor	0.9
THD	<20%
Lumens	4600
Luminous Efficiency	115 Lm/W
Color Temperature	4000K
CRI	83
Housing	24 Gauge Steel
Finish	White
Dimensions (Inches)	96"(L) x 3.4"(W) x 3.6"(D)
LIFESPAN & ENVIRONMENT	
Average Life	50,000
Operating Temperature	-20°C ~ 50°C



#### DIMENSIONS



#### DIMMER COMPATABILITY

Only the following dimmers have been tested, by no means is this list complete:

#### LUTRON

DIVADVSTV  
MAESTRO MS-Z101  
NOVA T NTSTV

#### LEVITON

ILLUMATECH IP710-LFZ

#### PHILIPS

SUNRISE SR1200ZTUNV

#### ORDERING

ITEM#	DESCRIPTION	WATTS	COLOR	LUMENS	CRI	VOLTS	HOURS	CASE
55136	LED 96" DESIGNER STRIP - 40W/40K/120-277V/DIMMABLE - SUPERIOR LIFE® DLC	40	4000K	4600	83	120-277	50,000	1