

# LED A19 Light Bulbs

40/60 Watt Incandescent Equivalent



## Product Features

- Omni-direction diffusing light beam at average 300°
- Instant on-No warm-up period
- No UV/IR light in the beam
- Available in 2700K and 4000K Color Temperature
- Excellent Color Rendering at >80
- 25,000 hours rated life, it will last 22.8 years based on 3 hours per day usage
- Limited 10 year replacement warranty
- For damp location
- Dimmable & compatible with major dimmer brands

## Environmental Commitment

- RoHS compliant – Contains no harmful lead or mercury
- Disposable with no environmental risk
- UV and IR free
- UL damp rated

## Energy Saving

Bulb Technologies	Annual Electricity Cost
40W Incandescent	\$4.80
6W LED PAR30	\$0.70
<i>Saving per bulb</i>	<b>\$7.80</b>
60W Incandescent	\$7.22
9W LED PAR38	\$1.08
<i>Saving per bulb</i>	<b>\$9.36</b>

Based on 3 hours per day usage and \$0.11 per Kwh.

## Omnidirectional Light Distribution Comparison



Curtis Mathes

Other LED Bulbs

Curtis Mathes A19 LED Omnidirectional A-Line lamps replicate true A19 incandescent with a 300-degree beam angle that produces even light in all directions.



## Specification

Model	CMA19L-1110	CMA19L-1313
Bulb Type	A19	A19
Rated Wattage	6W	9W
Luminous Flux	470lm	800lm
Color Temperature	2700K or 4000K	2700K or 4000K
Beam Angle	300°	300°
CRI	>80	>80
Power Factor	>0.8	>0.8
Input Voltage	100-120V 60Hz	100-120V 60Hz
Dimming Range	10%-100%	10%-100%
Base	E26	E26

## Packaging Information

Individual Box Dimension	62 x 62 x 117mm
Individual Box Gross weight	0.29 lbs
Master Carton Q'ty	50 pcs
Master carton Box dimension	334 x 332 x 254mm
Master carton box Gross weight	14.88 lbs
Quantity per GMA pallet	3600 pcs

## Ordering Information

Models	Color Temperature
CMA19L-1313-8XX	XX = 27 for 2700K
CMA19L-1110-8XX	XX = 40 for 4000K

Examples: CMA10L-1313-827 for 9W 2700K CCT A19 bulb.



## Dimmer List

Brands	Models
Lutron	DV-603P600W S-600 600W LGCL-153CL 600W S-600PR-WH 600W
Leviton	6631-LA 600W 6683 600W 6631-LA 600W IPI06 600W S-600P-WH
GE	18024 600W
ALMOND	LUXDM600-12 600W
Top	HCL453PTC HCL453PW

### Caution

1. Suitable for use in operating environments between  $-20^{\circ}\text{C}$  and  $+45^{\circ}\text{C}$  ( $-4^{\circ}\text{F}$  and  $+113^{\circ}\text{F}$ )
2. Not for use with emergency light fixtures or exit lights
3. Use in open fixture or fixtures with small air gaps for 3 hours a day.