A19 8.5W DIM. TITANIUM LED SERIES









- Omnidirectional: 330° beam angle
- Exceptional efficacy 94 LPW in Warm White
- 40% more energy savings than CFL
- Comfortable warm diffused light
- Natural A-lamp shape fits all applications
- Ideal for lamps with shades



















60W Inc.

80% Energy Savings

\$157 Savings per lamp*













A19 PRODUCT FEATURES

This A19 meets the new ENERGY STAR V1.1 requirements for omnidirectional bulbs by providing 330° of evenly distributed light intensity. In the 135° to 180° zone, this lamp emits 65% more lumens than what is required by ENERGY STAR, providing a fuller light than other LED A-lamps.





Exceptional Efficacy





At 94 LPW, this lamp's efficacy is more than 15% higher than the Tier 1 LED A19 60W replacement industry average and exceeds new ENERGY STAR requirements by upwards of 65%. This energysaving performance makes this lamp a smart retrofit choice for incandescent and CFL bulbs.


A19 8.5W DIM. TITANIUM LED SERIES



Ref.#: DS118-A19-8.5W







SPECIFICATIONS

Product Model	57856 8.5A19DIM/827	57857 8.5A19DIM/830	57858 8.5A19DIM/840
Туре	A19	A19	A19
Base	E26	E26	E26
Power (W)	8.5	8.5	8.5
Voltage - Frequency	120V 60Hz	120V 60Hz	120V 60Hz
Color Temp. (ANSI)	Soft White 2700K	Warm White 3000K	Cool White 4000K
CRI (Ra) (typ.)	80	80	80
Typical lumens (lm)	800	800	850
Efficacy (LPW)	<mark>(94</mark>)	94	100
Beam Angle	(330°)	330°	330°
Dimmable	(Yes**)	Yes**	Yes**
Power Factor	0.9	0.9	0.9
Rated Lifetime - L70 (hrs.)	25,000	25,000	25,000
Dia. x MOL	2.36"x4.35" (60x110mm)	2.36"x4.35" (60x110mm)	2.36"x4.35" (60x110mm)
Weight (lb. / g)	0.13lb. / 59g	0.13lb. / 59g	0.13lb. / 59g

^{**} Compatible with most major dimmers

*** Not intended for use in totally enclosed fixtures

**** Suitable for damp locations. Not for use where directly exposed to weather or water