



GE
Lighting

Commercial Products & Solutions

[SITE SEARCH](#) > [HOME](#) > [PRODUCTS](#) > [EDUCATION / RESOURCES](#) > [LIGHTING APPLICATIONS](#)

[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)

[Products](#) > [Compact Fluorescent](#) > [Indoor Floodlight](#) > 80893

80893 – FLE15/2/R30XL827

GE Floodlight Soft White R30 - Facilities; Retail Display; Hospitality; Office; Restaurant



a product of
ecomagination


High Color Rendering
cUL Listed

UL Listed



GENERAL CHARACTERISTICS

Lamp type	Compact Fluorescent - Self-Ballasted
Bulb	R30
Base	Medium Screw (E26)



[View Larger](#)

Wattage	15
Equivalent Wattage	65 W
Rated Life	10000 hrs
Starting Temperature (MIN)	-15 °C (5 °F)
Picograms of Mercury	467 picograms
Primary Application	Indoor Floodlight; Facilities; Retail Display; Hospitality; Office; Restaurant

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	750
Nominal Initial Lumens per Watt	50
Color Temperature	2700 K
Color Rendering Index (CRI)	82

ELECTRICAL CHARACTERISTICS

Input Voltage	120 V
Input Current	0.2300 A

DIMENSIONS

Maximum Overall Length (MOL)	5.5000 in (139.7 mm)
Nominal Length	5.500 in (139.7 mm)

PRODUCT INFORMATION

Product Code	80893
Description	FLE15/2/R30XL827

Standard Package	Case
Standard Package GTIN	10043168808931
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168808934

 CAUTIONS & WARNINGS

[See list of cautions & warnings.](#)
