



## SpringLight™ Compact Fluorescent

• NPF, 10,000 hours average rated life – SpringLamps®

Item #	Item Description	CFL Watts	Incandescent Wattage Comparison	Initial Lumens	Color Temperature	Input Line Current	M.O.L. (inches)	Diameter (inches)
801009	9W Mini Spring Light	9	40	540	2700K	.15A	4.0	1.8
8010093	9W Mini Spring Light 3 Pack	9	40	540	2700K	.15A	4.0	1.8
80100941 +	9 Watt Mini Spring Light 41K	9	40	440	4100K	.15A	4.0	1.8
801009413 +	9 Watt Mini Spring Light 41K 3 Pack	9	40	440	4100K	.15A	4.0	1.8
80100950 +	9 Watt Mini Spring Light 50K	9	40	405	5000K	.15A	4.0	1.8
801009503 +	9 Watt Mini Spring Light 50K 3 Pack	9	40	405	5000K	.15A	4.0	1.8
801014	14W Mini Spring Light	14	60	900	2700K	.20A	4.4	1.8
8010143	14W Mini Spring Light 3 Pack	14	60	900	2700K	.20A	4.4	1.8
80101441 +	14 Watt Spring Light 41K	14	60	800	4100K	.20A	4.4	1.8
801014413 +	14 Watt Spring Light 41K 3 Pack	14	60	800	4100K	.20A	4.4	1.8
80101450 +	14 Watt Spring Light 50K	14	60	630	5000K	.20A	4.4	1.8
801014503 +	14 Watt Spring Light 50K 3 Pack	14	60	630	5000K	.20A	4.4	1.8
801019	19W Mini Spring Light	19	75	1200	2700K	.31A	4.4	2.3
8010193	19W Mini Spring Light 3 Pack	19	75	1200	2700K	.31A	4.4	2.3
80101941 +	19 Watt Spring Light 41K	19	75	1100	4100K	.31A	4.4	2.3
801019413 +	19 Watt Spring Light 41K 3 Pack	19	75	1100	4100K	.31A	4.4	2.3
80101950 +	19 Watt Spring Light 50K	19	75	840	5000K	.31A	4.4	2.3
801019503 +	19 Watt Spring Light 50K 3 Pack	19	75	840	5000K	.31A	4.4	2.3
801023	23W Spring Light	23	100	1600	2700K	.38A	4.8	2.3
8010233	23W Spring Light 3 Pack	23	100	1600	2700K	.38A	4.8	2.3
80102341 +	23 Watt Spring Light 41K	23	100	1500	4100K	.38A	4.8	2.3
801023413 +	23 Watt Spring Light 41K 3 Pack	23	100	1500	4100K	.38A	4.8	2.3
80102350 +	23 Watt Spring Light 50K	23	100	1200	5000K	.38A	4.8	2.3
801023503 +	23 Watt Spring Light 50K 3 Pack	23	100	1200	5000K	.38A	4.8	2.3
801027	27 Watt Spring Light	27	100	1750	2700K	.46A	5.5	2.4
8010273	27 Watt Spring Light 3 Pack	27	100	1750	2700K	.46A	5.5	2.4
80102741 +	27 Watt Spring Light 41K	27	100	1650	4100K	.46A	5.5	2.4
801027413 +	27 Watt Spring Light 41K 3 Pack	27	100	1650	4100K	.46A	5.5	2.4
80102750 +	27 Watt Spring Light 50K	27	100	1300	5000K	.46A	5.5	2.4
801027503 +	27 Watt Spring Light 50K 3 Pack	27	100	1300	5000K	.46A	5.5	2.4

• NPF, 8,000 hours average rated life – Globes/A-Lamp/Floodlights

8060092 +	9 Watt G25 Globe 2 Pack	9	40	495	2700K	.15A	4.3	3.1
8060142	14 Watt G25 Globe 2 Pack	14	60	800	2700K	.23A	4.3	3.1
8070092	9 Watt A Lamp 2 Pack	9	40	450	2700K	.15A	4.1	2.2
8070142	14 Watt A Lamp 2 Pack	14	60	800	2700K	.23A	4.4	2.4
802014	14 Watt R20 Flood	14	50	495	2700K	.23A	4.3	2.5
803014	14 Watt R30 Flood	14	65	645	2700K	.23A	5.4	3.7
8030142	14 Watt R30 Flood 2 Pack	14	65	645	2700K	.23A	5.4	3.7
804023	23 Watt R40 Flood	23	120	1250	2700K	.38A	6.1	4.8
805023	23 Watt Par38 Flood	23	90	1200	2700K	.38A	6.2	4.8
8050232	23 Watt Par38 Flood 2 Pack	23	90	1200	2700K	.38A	6.2	4.8

+ Submitted for ENERGY STAR testing.

### Features and Benefits:

- Long life, 10,000 hour average rated life – SpringLamps®
- 8,000 hour average rated life – globes/a-lamp/floodlights
- Lasts 9 years, based on 3 hours use per day
- Lasts 10-13 times longer than incandescent
- Replace less often, ideal for hard to reach places
- Lower maintenance costs for lamp replacements
- Saves up to 75% in energy costs compared to similar light output incandescent lamps
- 2700°K color temperature closest to incandescent light
- Quick run-up time
- Medium base and compact height fits anywhere a standard incandescent fits
- Instant start, flicker free
- End of Life logic guards against violent failures
- World class phosphor insures high lumen output and excellent lumen maintenance
- Up to 23 watts approved for enclosed fixtures

### Applications:

Use anywhere a standard incandescent is used.  
Perfect for: Table Lamps, Floor Lamps, Ceiling Fixtures,  
Wall Sconces, Closet Lights and Desk Lamps

### Specifications (at full brightness)

End of Life Protection -----	Yes
Ballast Type -----	Electronic
Starting Method -----	Modified Rapid Start
Input Line Voltage -----	120VAC
Input Line Frequency -----	50/60HZ
Lamp Life (rated) -----	10,000 Hours/8,000 Hours
Color Temperature -----	2700°K
Color Rendering Index -----	82
Min. Starting Temperature -----	-20 ° F
Max. Operating Temperature -----	160 ° F
U.L. / C.U.L. Listed -----	Yes
FCC Compliance -----	47 C.F.R. Part 18
Lamp Operating Frequency -----	45 KHZ
Lamp Current Crest Factor -----	< 1.60
Max. Open Circuit Voltage -----	600V
Total Harmonic Distortion (NPF) -	< 150%
Power Factor -----	>.50



ISO 9002  
CERTIFIED

12 MONTH  
WARRANTY

TCP, Inc.

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-827-2211 | F: 330-995-6188 | www.tcp.com

©TCP, Inc. 2008/02/59