

# LED Flame-tip/Blunt-Tip Candle



60W Incandescent equivalent  
B13/CA13 Candelabra base bulbs.  
Energy Saving Enhanced to 90%

- Use 6 Watt of energy only
- High Color Rendering Index at 80
- Candelabra Base (E12)
- Up to 90% more efficient than incandescent bulb
- 2700K/3000K/4000K/5000K color temperature options
- Dimmable down to 5%
- Instant on- No warm-up period
- No UV/IR light in the beam
- Guarantee 25,000 hours rated life, it will last 22.8 years based on 3 hours per day usage
- Limited 10-year warranty

## Annual Overall Cost Saving

Bulb Technologies	Annual Electricity Cost	Over 25, 000 hours
60W Incandescent	\$7.23	\$165
6W LED bulb	\$0.72	\$16.5
<i>Saving per bulb</i>	<b>\$6.50</b>	<b>\$148.5</b>

Based on 3 hours per day usage and \$0.11 per Kwh.



## Applications

- Chandeliers
- Decorative lighting fixtures
- Wall sconces
- Operating temperatures: between -20°C to 30°C (-4°F to 86°F)

## UPC information



## Technical Data

Models	CM13-4501-8XX-B	CM13-4501-8XX-F
Bulb shape code	B13 Blunt-Tip	CA13 Flame-Tip
Rated Wattage	6W	6W
Incandescent Replacement	60W	60W
CRI	>80	>80
Color Temperature	2700K/3000K/4000K/5000K options	
Energy Star approval	No	Yes (Clear cover only)
Luminous Flux	450lm	450lm
Dimming	Yes	Yes
Base	E12	E12
Product dimension	(MOL) 4.69", (Diameter) 1.65"	(MOL) 4.9", (Diameter) 1.49"
Input Voltage	100V-120V /60Hz	95-135V /60Hz
Noise Level @10'	< 24 dBA	< 24 dBA

## Dimmer List

Brands	Dimmer Models
Lutron	S-600P, DV-600P, DVCL-153P, MACL-153M, CTCL-153P, CT-600P
Leviton	6633-P, 057, 6674, IPL06

## Packaging information

Models	CM13-4501-8XX-B	CM13-4501-8XX-F
Q'ty per Master carton	125 pcs	100 pcs
Master Carton Gross weight	8.5 kg	7.5 kg
Master Carton Dimension	545x230x230 mm	
Q'ty per GMA Pallet	10,000	8,000

## Ordering information

SKU Numbers	Bulb Shape	Finish	Wattages	Color Temperature
CM13-4501-8XX-BC	Blunt-Tip	Clear	6W	XX =27 for 2700K
CM13-4501-8XX-BF	Blunt-Tip	Frosted		XX =30 for 3000K
CM13-4501-8XX-FC*	Flame-Tip	Clear		XX = 40 for 4000K
CM13-4501-8XX-FF	Flame-Tip	Frosted		XX = 50 for 5000K

\* Energy Star rated

*Curtis Mathes. Life | Always On.™*

Information provided is subject to change without notice. Please verify all details with Curtis Mathes. All values are design or typical values when measured under LM-79 laboratory conditions, and Curtis Mathes makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions