



Dimmer Compatibility Guide

PLEASE NOTE: Compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment. Actual results may vary.

Product Family Name:	Filaments Curved: Fully Compatible Dimming			
Item Number:	776509	776510	776511	776512
Ordering Code:	LED4A19/22K/FIL-NOS/CURV/VICTOR	LED2ST18/22K/FIL-NOS/CURV/1890	LED4T14/22K/FIL-NOS/CURV/SPIRAL	LED4G25/22K/FIL-NOS/CURV/SPIRAL
				LED4ST18/22K/FIL-NOS/CURV/1890

Lamps per Dimmer

	Manufacturer	Product	Model Number	Overall Rating	Recommended Minimum	Maximum Tested*	Notes
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	IlumaTech	IPI06	Best	1	6	Dims down to 12%
		SureSlide	6633-P	Best	1	6	Dims down to 5%
		Vizia	VPI06-1LZ	Good	1	6	Shimmering at LE 2, dims down to 7%
	Lutron	Toggler	TG-600	Best	1	6	Dims down to 12%
		Diva	DV-600	Best	1	6	Dims down to 3%
		Skylark	S-600	Best	1	6	Dims down to 2%
		Maestro	MAW-600	Good	1	6	2+ minimum load, shimmering at LE 1-2, dims down to 2%
	Legrand	Titan	CD703-PW	Good	1	6	Shimmering at Med 1-2, dims down to 15%
		Titan	CDLV703-PW	Good	1	6	Minor flicker at HE 1-2, dims down to 12%
		Harmony	D703-PTC	Good	1	6	Shimmering at LE 1-2, dims down to 2%
		Harmony	H703-PTC	Good	1	6	Shimmering at Med 1-2, dims down to 7%
CFL/LED	Leviton	IlumaTech	IPL06	Best	1	6	Dims down to 1%
		Sureslide	6674	Best	1	6	Dims down to 10%
		Decora	6672	Best	1	6	Dims down to 10%
	Lutron	Diva	DVCL-153PL	Best	1	6	Dims down to 1%
		Toggler	TGCL-153PH	Best	1	6	Dims down to 1%
		Maestro	MACL-153MLH	Best	1	6	Dims down to 1%
		Skylark	CTCL-153	Best	1	6	Dims down to 1%
		Skylark	SCL-153P	Best	1	6	Dims down to 1%
		Radio RA	RA2RR-6CL-PD	Best	1	6	Dims down to 1%
	Legrand	Harmony	DCL453-PTC	Best	1	6	Dims down to 15%
		Harmony	HCL453PTC	Best	1	6	Dims down to 10%
		Adorne Paddle	ADPD453LM2	Good	1	6	Dims down down to 22%
Electronic Low Voltage	Leviton	Vizia	VPE04	Good	1	6	Minor flicker LE to HE 1-6, dims down to 10%
		IlumaTech	IPE04	Good	1	6	Minor flicker LE to Med 1-6, dims down to 5%
		Decora	6615-P	Good	1	6	Minor flicker LE to Med 1-6, dims down to 25%
	Lutron	Skylark	SELVB-300P	Good	1	6	Minor flicker LE to Med 1-6, dims down to 10%
		Skylark Countour	CTELV-303P	Good	1	6	Minor flicker LE to Med 1-6, dims down to 10%
		Diva	DVELV-300P	Good	1	6	Minor flicker LE to Med 1-6, dims down to 10%
		Maestro	MAELV-600	Good	1	6	Minor flicker LE to Med 1-6, dims down to 10%
	Legrand	VIERTI	VTEL-600M-W	Best	1	6	Dims down to 10%
		Scene Director	SCELV	Good	1	6	Dims down to 20%
		Magentic Low Voltage	Vizia	VPM-06	Good	1	6
Decora	6613-P		Best	1	6	Dims down to 7%	
Maestro	MALV-600		Good	1	6	2+ minimum load, dims down to 6%	
Legrand	Harmony		DLV703-PW	Good	1	6	Minor flicker LE to HE 1-2, dims down to 4%
Universal	Legrand	Adorne SoftTap	ADTP703TU	Best	1	6	Dims down to 15%
		Miro Decorator	DRD4-W	Good	1	6	Shimmering LE 1, dims down to 5%
		Harmony	H703PTUTC	Good	1	6	Dims down to 20%
		Adorne Whisper	ADWR700MMTUM2	Best	1	6	Dims down to 1%
	Cooper	Adorne Touch	ADTH700MMTUM2	Best	1	6	Dims down to 1%
		Decorator	DAL06P-C2-K-L	Good	1	6	Minor flicker at LE 1-6, dims down to 12%
		Skye	SAL06P-W-K-L	Good	1	6	Minor flicker at LE 1-6, dims down to 1%

*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.

†May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating	
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.
Good	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBA), wide dimming range - can dim down to 20% or less of light output.
High End (H.E.) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.
Low End (L.E.) Dead Travel	