

FULHAM®

HOTSPOTLED™

HotSpot1 LED Emergency Lighting Kits



- Quick plug-n-play room-side installation
- Revolutionary design for extreme versatility
- UNV and many battery options for superior adaptability
- High efficiency, high lumen output LEDs for cost effectiveness

Fulham's HotSpot1 kits provide easy-to-install emergency LED lighting for common troffer installations, including T5 and T8 LED tube retrofits. They are UL Classified for field or factory installation, with a range of battery and module options to fit any situation. Each kit includes a HotSpot1 emergency LED driver, battery pack, LED module, required hardware, the necessary UL Classified label (to secure to the fixture after installation), and complete installation instructions.



HotSpot1 kits for troffers include an emergency driver, battery, LED module, installation instructions, and all necessary hardware and labels. The kits are not electrically connected to the normal lumination source. Choose the right kit for the job according to the required lumen output, run time, and module dimensions. Contact Fulham for details.

Common Specifications			
Input Voltage	120V-277V (UNV)	Output Short Circuit Protection	Self Resetting PTC
Surge Protection	C62.41 (TVS)	Recharge Time Required	24 hours
Over Current Protection	Fuse	Battery Type	NiCd 3.6VDC
Input Current	0.07A	Illumination Time	Minimum 90 minutes
Input Power	<4W	Output Classification	UL 1310 / Class 2
Output Voltage	3.6V	Ambient Temperature	0°C - 50°C

UL Classified Kits					
Model Number	Watts	Lumen Output	Estimated Run Time	Module Type	Module Dimensions (LxW)
FHSKITT03LNC	3	450	145 Mins	Linear	4.68" x 0.82"
FHSKITT03LND	3	450	200 Mins	Linear	4.68" x 0.82"
FHSKITT03LNF	3	450	360 Mins	Linear	4.68" x 0.82"
FHSKITT03LNFL†	3	450	360 Mins	Linear	4.68" x 0.82"
FHSKITT04LNC	4	500	145 Mins	Linear	4.68" x 0.82"
FHSKITT04LND	4	500	200 Mins	Linear	4.68" x 0.82"
FHSKITT04LNF	4	500	360 Mins	Linear	4.68" x 0.82"
FHSKITT06SHC	6	750	90 Mins	Small-H	3.54" x 3.93"
FHSKITT06SHD	6	750	125 Mins	Small-H	3.54" x 3.93"
FHSKITT06SHF	6	750	235 Mins	Small-H	3.54" x 3.93"
FHSKITT07LND*	7	900	100 Mins	Linear	4.68" x 0.82"
FHSKITT07LND*	7	900	180 Mins	Linear	4.68" x 0.82"
FHSKITT07LNFL*†	7	900	180 Mins	Linear	4.68" x 0.82"
FHSKITT08LHD	8	1000	90 Mins	Large-H	5.71" x 3.93"
FHSKITT08LHF	8	1000	175 Mins	Large-H	5.71" x 3.93"
FHSKITT10LHF	10	1250	135 Mins	Large-H	5.71" x 3.93"
FHSKITT10SHF	10	1250	135 Mins	Small-H	3.54" x 3.93"
FHSKITT10LNF**	10	1350	120 Mins	Linear	4.68" x 0.82"
FHSKITT10LNFL**†	10	1350	120 Mins	Linear	4.68" x 0.82"

*Includes 2 linkable 450lm linear modules

** Includes 3 linkable 450lm linear modules

†Linear Battery