PL H 5.5W DIR TITANIUM LED SERIES











- Easy to install Plug & Play Direct
- Ballast output power control technology
- Exceptional efficacy 102 LPW
- Compatible with most electronic ballasts
- Available in 2700K, 3000K, 3500K & 4000K CCT























PL PRODUCT FEATURES

High Performance - Ballast Smart Control

The PL DIR lamp's ballast smart control technology allows for high performance even on lower powered ballasts, making it a suitable replacement for 13W and 18W CFL PL lamps.

Ballast Type	Lumens	Bare Lamp
13W	550	5W
18W	560	5.5W


Adjustable Base





This PL H lamp features a base that can be rotated 310° to fit any socket configuration. After installation simply rotate the lamp to achieve maximum light output.

PL H 5.5W DIR TITANIUM LED SERIES










G24q & GX24q (4-pin CFL) Base: **Ballast compatible 120-277V** Voltage:

PF: 0.9

Lifetime: 50,000 hrs Weight: 0.15lb / 68g



SPECIFICATIONS*

Model	Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
5.5PLH/827/DIR	57895	5.5	Soft White 2700K	80	520	95	110°
5.5PLH/830/DIR	57896	5.5	Warm White 3000K	80	550	100	110°
5.5PLH/835/DIR	57897	5.5	Neutral White 3500K	80	550	100	110°
5.5PLH/840/DIR	57898	5.5	Cool White 4000K	80	560	102	110°

BALLAST PERFORMANCE

Ballast Type	Bare Lamp (W)	System (W)	2700K Lumens	3000K Lumens	3500K Lumens	4000K Lumens
13W	5	6.7	480	500	500	550
18W	5.5	7.5	520	550	550	560

Testing Method: Power and lumen output will vary based on number of lamps, ballast and fixture type. Above data is indicative only.

^{*} Specification data is preliminary and may be subject to change
** Suitable for damp locations. Not for use where directly exposed to weather or water

^{***} Not intended for use in enclosed fixtures
**** Full installation guide and more details available on website