

LED A19 800lm Light Bulbs

Energy Star & UL Certified for enclosed fixtures
60W Incandescent Equivalent



Product Features

- Suitable for enclosed fixtures such as Jelly jar, ceiling light, wall sconce, recessed downlight or wall lantern fixtures
- Available in 2700K/3000K/4000K Color Temperature options
- Color Rendering index > 82
- Beam angle: 230°
- 25,000 LED lumen life hours, it will last 22.8 years based on 3 hours per day usage or 5.7 years based on 12 hours per day usage
- Limited 5-year replacement warranty
- Suitable for damp and dry locations
- (MOL) 4.2", (bulb diameter) 2.37"
- Does not support dimmers
- E26 Edison Screw base

Application Notes

- Suitable for use in enclosed fixtures such as Jelly jar
- $\geq -4^{\circ}\text{F}$ to $\leq 120^{\circ}\text{F}$ is the rating for the ambient temperature inside an enclosed fixture.
- Suitable for indoor lighting application
- Does not support dimmers
- The led lumen life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

Suitable for enclosed fixtures

Most LED Bulbs carry a strong warning about not to use the bulb in a fully enclosed fixture because light bulb life expectancy will be shortened by the overheat temperature operating inside the lamp fixtures. Conversely, Curtis Mathes A19 light bulbs are designed to operate safely in totally enclosed such as jelly jars, ceiling mount fixtures, recessed downlight fixtures and etc. It also withstands the ambient heat built up inside the lamp fixtures while also not sacrificing the lumen maintenance. Curtis Mathes A19 light bulbs for enclosed fixtures have passed UL enclosed chamber tests.



Energy Saving

Bulb Technologies	Annual Electricity Cost	Over 25,000 hours
60W Incandescent	\$7.23	\$165.00
9W LED bulb	\$1.08	\$24.80
Saving per bulb	\$6.14	\$140.30

Based on 3 hours per day usage and \$0.11 per Kwh.

Ordering Information

Models	Watt	Case Q'ty	Initial Lumen	Input Voltage	CRI	Rate Life*	Color Temperature
CMA19-1321-8XX	9W	1	800	100-130V	>82	25,000 hrs	XX = 27 for 2700K
CMA19-1324-8XX	9W	4	800	100-130V	>82		XX = 30 for 3000K
CMA19-1326-8XX	9W	6	800	100-130V	>82		XX = 40 for 4000K

For example, CMA19-1321-827

* The led lumen life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

Packaging Information

1-Pack Case dimension	CMA19-1321-8XX
Q'ty per Master Carton	50 Units
Master carton Dimension	325x325x230 mm
Master carton gross weight	7.27 lbs (3.3kg)

4-Pack Case	CMA19-1324-8XX
4-Pack Case Gross weight	0.56 lbs (0.25kg)
Case Q'ty/Master Carton	20 cases
Total Bulbs/Master carton	80 units
Master carton Dimension	505x320x190 mm
Master carton gross weight	11.2 lbs (5.1kg)

6-Pack Case	CMA19-1326-8XX
6-Pack Case Gross weight	0.823 lbs (0.38kg)
Case Q'ty/Master Carton	20 cases
Total Bulbs/Master carton	120 units
Master carton Dimension	590x360x245 mm
Master carton gross weight	16.7 lbs (7.6kg)

UPC information

SKU	UPC	Pack
CMA19-1321-827	8 11019 02150 0	1
CMA19-1321-830	8 11019 02151 7	1
CMA19-1321-840	8 11019 02152 4	1

SKU	UPC	Pack
CMA19-1324-827	8 11019 02153 1	4
CMA19-1324-830	8 11019 02129 6	4
CMA19-1324-840	8 11019 02154 8	4

Curtis Mathes. Life | Always On.™