

# LED A19 for enclosed fixtures

## 75W-equalvalent



### Features

- A19 shape
- Delivers 1100lm, equivalent to 75W incandescent
- Available in 3000K/5000K Color Temperature options
- UL and Energy Star certified for totally enclosed fixtures
- Color Rendering index > 82
- Beam angle: 230°
- Dimmable and works with Lutron Caséta wireless dimmer PD-6WCL
- Energy Star rated
- 15,000 LED life hours\*, the lumen will last 13.6 years based on 3 hours per day usage or 3.42 years based on 12 hours a day usage.
- Limited 5-year replacement warranty
- Instant on - No warm-up period
- Suitable for damp locations
- Contain no harmful lead or mercury

### Suitable for enclosed fixtures

Most LED Bulbs carry a strong warning about not to use the bulb in a fully enclosed fixture because light bulb life expectancy will be shortened by the overheat temperature operating inside the lamp fixtures. Conversely, Curtis Mathes A19 light bulbs are designed to operate safely in totally enclosed such as jelly jars, ceiling mount fixtures, recessed downlight fixtures and etc. It also withstands the ambient heat built up inside the lamp fixtures while also not sacrificing the lumen maintenance. Curtis Mathes A19 light bulbs for enclosed fixtures have passed both the Energy Star and UL enclosed chamber tests.

### Energy Cost

Bulb Technologies	Annual Electricity Cost	Over 25,000 hours
75W Incandescent	\$9.03	\$123.80
11W LED A19	\$1.45	\$35.80
Saving per bulb	<b>\$7.59</b>	<b>\$104.00</b>

Based on 3 hours per day usage and \$0.11 per Kwh.



### Application Notes

- Suitable for use in enclosed fixtures such as Jelly jar
- $\geq -4^{\circ}\text{F}$  to  $\leq 120^{\circ}\text{F}$  is the rating for the ambient temperature inside an enclosed fixture.
- Suitable for indoor lighting application and damp environments

\* The Led lumen life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

## Compatible Dimmer List

Brands	Models	Part Numbers
Lutron	Toggler	TGCL-153PH-WH
	Toggler	CTCL-153P
	Skylark	CTCL-183PHD-WH
	Skylark	CTCL-183PH-WH-C
	Skylark	C.L SCL-153PH
	Caséta	PD-6WCL
	Maestro	MACL-153M, MACL-153MH
	Maestro	MSCL-OP153MH
	Diva	DVWCL-153P, DVWCL-153PH
	Diva	DV-600P, DV-600PR-WH
	Luméia	LGCL-153PH-WH-C
	Luméia	LGCL-153PLH
	Credenza	TT-300NLH-WH-CSA
Leviton		6681-W, 6683
Cooper	AL Series	SAL06-A-K-L
Legrand	Radiant	RHCL453P, RHCL453PNICCV4

## Packaging Information

Master Carton Q'ty	50 pcs
Master carton Dimension	325x325x230 mm
Master carton gross weight	6.83 lbs (3.1kg)

## Ordering Information

Models	Wattages	Input	Lumen	CRI	Color Temperature options
CMA19-7502-8XX	11W	100-120V	1100lm	>80	XX = 30 for 3000K XX = 50 for 5000K

For example, CMA19-7502-830: 11W A19 in 3000K color temperature

*Curtis Mathes. Life | Always On.™*

Information provided is subject to change without notice. Please verify all details with Curtis Mathes. All values are design or typical values when measured under laboratory conditions, and Curtis Mathes makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions