



PL-C Cluster 4-Pin Base Energy Advantage

PL-C 26W/827/XEW/4P/ALTO 21W

Philips Linear Compact Fluorescent Lamps offer designers, specifiers and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities. With so many elegant fixtures available to complement their small size, high light output and advanced technology, Philips Energy Advantage lamps are fast becoming the preferred choice when maximum effciency and sleek design solutions are required.

Product data

General Information			
Cap-Base	G24Q-3 [G24q-3]		
Life To 50% Failures Preheat (Nom)	12000 h		
LSF Preheat 2000 h Rated	99 %		
LSF Preheat 4000 h Rated	98 %		
LSF Preheat 6000 h Rated	97 %		
LSF Preheat 8000 h Rated	90 %		
Light Technical			
Color Code	827 [CCT of 2700K]		
Initial lumen (Nom)	1800 lm		
Luminous Flux (Rated) (Nom)	1800 lm		
Color Designation	Incandescent White		
Chromaticity Coordinate X (Nom)	455		
Chromaticity Coordinate Y (Nom)	415		
Correlated Color Temperature (Nom)	2700 K		
Luminous Efficacy (rated) (Nom)	75 lm/W		
Color Rendering Index (Nom)	82		

LLMF 2000 h Rated	92 %	
LLMF 4000 h Rated	88 %	
LLMF 6000 h Rated	86 %	
LLMF 8000 h Rated	84 %	
LLMF 12000 h Rated	81 %	
Operating and Electrical		
Power (Rated) (Nom)	24.0 W	
Lamp Current (Nom)	0.300 A	
Temperature		
Design Temperature (Nom)	28 °C	
Controls and Dimming		
Dimmable	Yes	


Datasheet, 2016, December 22 data subject to change

PL-C Cluster 4-Pin Base Energy Advantage

Mechanical and Housing					
Cap-Base Information	4P				
Approval and Application					
Energy Efficiency Label (EEL)	В				
Mercury (Hg) Content (Nom)	1.4 mg				
Product Data					
Order product name	PL-C 26W/827/XEW/4P/ALTO 21W				

EAN/UPC - Product	046677220426 220426			
Order code				
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	10			
Material Nr. (12NC)	927906782720			
Net Weight (Piece)	60.400 g			
ILCOS Code	FSQ-26/27/1B-E-G24q=3			

Dimensional drawing



PL-C ALTO 26W/827/4P

Product	D	D1	Α	В	С
PL-C 26W/827/XEW/4P/ALTO 21W/	27 1 mm	27 1 mm	130.7 mm	1/10 ft mm	163 0 mm

