

PRO

G25

Decorative LED Globe

EQUIVALENT TO 40 OR 60W INCANDESCENT



LOW POWER CONSUMPTION

Save money and improve your energy efficiency with this low power consuming lamp that delivers BIG on light!

OMINIDIRECTIONAL LIGHT

Approximately 300° beam angle gives you smooth, clean light

ENERGY STAR RATED

SIMPLE, POWERFUL, FLEXIBLE light that gives you illumination how and where you need it. This amazing little lamp gives you crisp clear light using only 4.5 or 6W of energy. Also, given it's omni-directional design you can count on maximum light in all the right areas.



OMNI-DIRECTIONAL

Clear, crisp, even light for all your environments

USES ONLY 4.5 or 6W ENERGY

Energy efficient and contains no harmful chemicals like mercury and lead.

ENERGY STAR RATED

A rating you can trust for quality

LIGHTING SCIENCE



ORDERING INFORMATION

FAMILY	PRODUCT	WATTAGE EQUIVALENT	COLOR TEMPERATURE	LENS	VOLTAGE	PACKAGING
LSPRO	G25	40WE	W27 - 2700K	LP FR - FROSTED	120 - 120VAC	BX - BOX
		60WE				

example: LSPRO G25 60WE W27 LP FR 120 BX

PRODUCT NAME: LSPRO G25

SPECIFICATIONS ¹	W27	
Color Temperature ²	2700K	
Equivalent Source Standard	40WE	60WE
Output (Lumens) ³	379	560
Power Consumption	4.5W	6W
Power Factor	0.9	0.9
CRI	81	80
R9	6	1
Beam Angle	Omnidirectional (~ 300°)	
Input Voltage	120VAC	
Dimmable ⁴	Yes	
Construction	Polymer	
Base	E26	
Dimensions (Length x Diameter)	4.61 x 3.3 in (117 x 83 mm)	
Weight	0.33 lbs (0.15 kg)	
Lumen Maintenance ⁵ (L ₇₀)	25,000	
Warranty	5 Year Limited	
Environment	Damp	
Certifications	Energy Star; RoHS; UL Listed	

Dimmer Compatibility List:

Lutron LED - Skylark Contour® C-L, Maestro® C-L MACL-153M, Maestro Wireless® C-L MRF2-6CL, Caséta Wireless® C-L PD-6WCL, Diva® C-L DVCL-153P, Ariadni® C-L AYCL-153P, Lumea® C-L LGCL-153P

Lutron Incand. - Diva® DV-600P

Leviton UNV - SureSlide® 6674, SureSlide® 6672, Decora® Rocker Slide DSM10-1LZ, IllumaTech® Slide IPL06-10Z

Leviton ELV - Decora® Rocker Slide DSE06-10Z

Eaton-Copper LED - Aspire 9573

Eaton-Copper Incand. - Aspire 9530

Legrand Pass & Seymour UNV - Harmony® Tru-Unv H703PTUW

¹ Specifications and values supplied are nominal and are subject to change without notification

² Color temperatures conform to nominal CCTs as defined in ANSI Chromaticity Standard C78.377A

³ Lumen measurement complies with IES LM-79-08 testing procedures

⁴ See compatibility list for list of compatible dimmers.

⁵ Lumen maintenance calculations are based on measurements that comply with IES LM-80-08 testing procedures. L70 = 70% lumen maintenance, or when lamp reaches 70% of initial output