



C SERIES

Medium Body Strip



X1 LED

The most economical, practical and user friendly series of LED fixtures with the energy savings, quality of light, long life and hassle-free maintenance. X1 LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required) and have flexibility to change wattage and color temperature any time. Fixture performance will evolve over time with the evolution of the T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture, X1 LED solves that by utilizing a self contained LED lamp that fits into fixture just like a fluorescent lamp.

This medium body strip for interior warehouse, retail, and utility areas requiring general illumination in a commercial quality strip configuration is an ideal application for X1LED. While LED arrays with separate driver can be very bright and glary when not diffused, LED T8 lamps are bright but comfortable to look at. The X1LED linear strip fixtures utilize efficient LED T8 lamps that provide high lumen output with efficient energy savings. Since they don't require any ballast or driver the only component that will ever need changing is the LED T8 lamp. Unlike linear strip fixtures that utilize LED arrays and drivers these fixtures have the flexibility to change wattage, lumens, and color temperature simply by changing the lamps without the need to call a licensed electrician.

LAMP

1, 2, or 3 Lamp Positions in Cross section

CONSTRUCTION

Housing is die-formed and embossed code 22 gage steel. Finish is high reflectance baked white enamel. Wiring knockouts are provided on back and end of housing. Ballast covers or reflectors attach without tools to simplify ballast access.

- Single unit length and tandem fixtures available in most lamp styles.
- End plate doubles as coupler for continuous row mounts.

ELECTRICAL

Meets UL1598 for continuous row mounting and comes with provision for a coupling method.

MOUNTING

Surface mount, chain hung, double stem

SIZE W x L x H in inches (mm)

4.25W x 2.00H (110 x 50)

Fixture length = lamp(s) length

ITEM NO.	DESCRIPTION
C217X1	2ft. 2 Light Strip Ready for LED T8 Bypass Lamps
C317X1	2ft. 3 Light Strip Ready for LED T8 Bypass Lamps
C232X1	4ft. 2 Light Strip Ready for LED T8 Bypass Lamps
C332X1	4ft. 3 Light Strip Ready for LED T8 Bypass Lamps
C2328X1	8ft. 4 Light Tandem Strip for LED T8 Bypass Lamps

Fixtures above wired for single ended power. Use with LED T8 lamps with internal driver.

