



Titanium Series T5 HO 24W DIR

For models: 24T5HO/4F/xxx/DIR Where xxx means 818-965 which indicates CRI and color temperature

Emergency Ballast Compatibility

	3 7 1	
Brand	Model	Lumens (Single Lamp Wired on Emergency)
		24T5HO/4F/830/DIR
Bodine	LP600	357
Bodine	LP550	237
Bodine	B100	158
Bodine	B60	186
Bodine	B54	167
Bodine	B30ST	862
lota	I-320	582
lota	I-232	309
lota	I-162	606
lota	I-42-EM-R-J	213
lota	I-32	260
lota	I-26-EM-A	364
lota	ISL-540	306
lota	ISL-54	234
lota	ICE-80	535
lota	ISD-80	216
Lithonia	PSQ500QD	150
Lithonia	PS1400QD	348
Lithonia	E1500 M12	156
Fulham	FH4-DUAL-700L	141
Fulham	FH5-DUAL-1400L	190
ALP	EFP 32GS	156

*GREEN CREATIVE has provided this emergency ballast compatibility chart for guidance when selecting an emergency ballast and lamp combination. Lamps were tested for compatibility with the above listed emergency ballasts. Emergency ballasts that do not appear on the chart might still be compatible but have not been tested. All testing has been performed with a stable main supply. The quality of the local main, existing installation and wiring, as well as different manufacturer versions of the above ballasts may affect lamp performance. Since no assurance can be provided regarding these factors, it is a general recommendation to perform a test on-site prior to installing the LED lamps.