



T12 LINEAR FLUORESCENT LOW MERCURY/ENVIRO-LUME™

Enjoy top lamp performance with Superior Life® fluorescent lamps. Built stronger to last longer, these lamps outperform the competition, giving you the best overall value for a superior product.

- **ENERGY EFFICIENT**

use about 1/5 as much electricity as an incandescent lamp to produce the same amount of light. Not impacted by new DOE energy efficiency targets.

- **ENHANCED COLOR**

up to 90 CRI (Color Rendering Index) provides excellent color consistency throughout the life of the lamp

- **BALLAST COMPATIBILITY**

Direct retrofit for existing T12 lighting, operates on both magnetic or electronic ballast.

LOW MERCURY ENVIRO-LUME™ CERTIFIED



All of our Superior Life® linear fluorescents are certified to protect the environment and allow for convenient domestic disposal.

ENVIRONMENTAL FEATURES:

- Passes EPA tests for substances that might dissolve into the ecosystem.
- 80% less mercury protects the environment from excess mercury in discarded lamps. Use a cleaner, low-mercury gas for a more crisp, clean light output Approved for domestic disposal.
- Saves money on lamp disposal costs and offers you more disposal options.
- Krypton/Argon Gas mixture for reduced energy consumption.
- No loss in performance – high efficiency offers the same color temperature as a standard fluorescent lamp.

E EISA COMPLIANT - Meets United States Minimum Efficiency Standards.

Hg This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.

**TCLP
COMPLIANT**



GO GREEN

Ordering Information

ITEM#	DESCRIPTION	WATTS	COLOR	LUMENS (INITIAL)	LUMENS (MEAN)	CRI	LENGTH (INCHES)	BASE	HOURS (AVERAGE)	CASE
90106	F40T12/CW/ENVIRO-LUME - SUPERIOR LIFE®	40	4100K	2650	2320	90	48	MED BI PIN	36,000	30
90107	F40T12/CW/ENVIRO LUME - SUPERIOR LIFE®	40	4100K	2600	2392	90	48	MED BI PIN	24,000	30
90108	F40T12/DAY-BRITE™ - ENVIRO-LUME	40	6500K	2400	2125	91	48	MED BI PIN	36,000	30
90162	F60T12/CW - SUPERIOR LIFE®	50	4100K	3800	3256	62	60	SINGLE PIN	12,000	15
90165	F72T12/CW - SUPERIOR LIFE®	56	4100K	4450	3900	62	72	SINGLE PIN	12,000	15
90121	F96T12/CW/ENVIRO-LUME - SUPERIOR LIFE®	75	4100K	5075	4350	90	96	SINGLE PIN	20,000	15
90163	F60T12/CW/HO - SUPERIOR LIFE®	75	4100K	4945	4500	82	60	RDC	12,000	15
90135	F96T12/CW/HO-O - SUPERIOR LIFE®	110	4100K	8800	7650	62	96	RDC	12,000	15
90136	F96T12/DAY-BRITE™/HO - SUPERIOR LIFE®	110	6500K	6750	5800	90	96	RDC	12,000	15
T12 U-BEND										
90111	FB40T12/CW/U/6 - SUPERIOR LIFE®	40	4100K	2200	2024	90	22.5	MED BI PIN	18,000	12

INITIAL LUMENS: Lumen output based upon the performance after 100 hours of operating life.

MEAN LUMENS: Lumen output at 40% of the lamps rated average life.

AVERAGE LIFE: Lamps turned off and restarted no more frequently than once every 3 operating hours, lamp life can be considerably longer if started less frequently.

WARRANTY: Lamps are warranted for 24 months.

E EISA COMPLIANT - Meets United States Minimum Efficiency Standards.

Hg This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.

