

# TWIN PLUG IN CFL



## 2 Pin Twin (Single) Tube CFL - Suitable for Preheat Magnetic Ballast

Nominal Wattage	Model #	Generic Designation	Item Description & CCT	Lamp Base	Initial Lumen	Average Rated Life (Hrs.)	Length/ MOL (Inches/mm)	Pack Inner/ Master	Item #
5	ODS5W/27K	CFT5W/G23/827	5W Twin CFL -2Pin - 2700K	G23	250	10,000	4.1 / 105	25 / 100	000
5	ODS5W/41K	CFT5W/G23/841	5W Twin CFL -2Pin - 4100K	G23	250	10,000	4.1 / 105	25 / 100	001
7	ODS7W/27K	CFT7W/G23/827	7W Twin CFL -2Pin - 2700K	G23	400	10,000	5.3 / 135	25 / 100	002
7	ODS7W/41K	CFT7W/G23/841	7W Twin CFL -2Pin - 4100K	G23	400	10,000	5.3 / 135	25 / 100	003
9	ODS9W/27K	CFT9W/G23/827	9W Twin CFL -2Pin - 2700K	G23	600	10,000	6.6 / 167	25 / 100	004
9	ODS9W/41K	CFT9W/G23/841	9W Twin CFL -2Pin - 4100K	G23	600	10,000	6.6 / 167	25 / 100	005
13	ODS13W/27K	CFT13W/GX23/827	13W Twin CFL -2Pin - 2700K	GX23	825	10,000	7.0 / 178	25 / 100	006
13	ODS13W/35K	CFT13W/GX23/835	13W Twin CFL -2Pin - 3500K	GX23	825	10,000	7.0 / 178	25 / 100	007
13	ODS13W/41K	CFT13W/GX23/841	13W Twin CFL -2Pin - 4100K	GX23	825	10,000	7.0 / 178	25 / 100	008
13	ODS13W/50K	CFT13W/GX23/850	13W Twin CFL -2Pin - 5000K	GX23	825	10,000	7.0 / 178	25 / 100	009

## 4 Pin Twin (Single) Tube CFL - Suitable for Electronic Ballast

13	• ODS13W/4P/27K	CFT13W/2GX7/827	13W Twin CFL - 4Pin - 2700K	2GX7	840	12,000	6.3 / 160	25 / 100	010
13	• ODS13W//4P/41K	CFT13W/2GX7/841	13W Twin CFL - 4Pin - 4100K	2GX7	840	12,000	6.3 / 160	25 / 100	011

## 2 Pin Twin (Single) Tube CFL - Flicker Free / Instant Start

13	ODS13W/FF/27K	CFT13W/GX23/827	13W Twin CFL -2Pin - 2700K Flicker Free	GX23	825	12,000	7.0 / 178	25 / 100	124
----	---------------	-----------------	--	------	-----	--------	-----------	----------	-----

### Applications



WALL SCONE



CEILING



TABLE/ FLOOR LAMPS



READING LAMP



RECESSED CANS



OUTDOOR COVERED



### Features

- 10,000 to 12,000 hour average rated life reduces relamping & related costs
- Rare earth tri-phosphor with 80 plus CRI for better performance
- High Luminous Efficacy
- 75% Lower Power Consumption over incandescent bulbs
- Available in various color temperature
- Compact Size

### Notes

- 4-Pin lamps are designed for Dimming & electronic applications
- Minimum Starting Temperature is also very much dependent on ballast.
- Available in various color temperature also (upon request)
- Equipment manufacturer are suggested to consult ANSI or IEC standard for maximum allowable dimensions & temperature for the optimum performance of the product.