

5.5" ROUND DOWNLIGHT 10W TITANIUM LED SERIES



10W REPLACES



65W Inc.

80% Energy Savings

CRISP



\$190 Savings per lamp*

- ⌚ Innovative **CLICK** design
- ⌚ **SootheOptic** low glare technology
- ⌚ Fits most 4" J-boxes and 6" recessed housings
- ⌚ Installs in just minutes - no rewiring
- ⌚ **Wet location rated**
- ⌚ Exceptional color rendering **CRI 90**



50,000 H



DIMMABLE



LOW GLARE



5 YR WARRANTY



CRI (Ra)



WET LOCATION



DOWNLIGHT PRODUCT FEATURES

Edge Lighting Technology

The CLICK DESIGN SURFACE MOUNT SQUARE & ROUND DOWNLIGHTS use the latest in edge lighting technology to produce a smooth uniform lighting effect. These naturally low glare downlights integrate seamlessly into all ceiling applications.




- BACK PLATE
- WATERPROOF FOAM
- EDGE LIGHTING REFLECTOR
- LIGHT GUIDE PLATE
- **SootheOptic** LOW GLARE
- TRIM

SootheOptic Low Glare Technology

These downlights all feature SootheOptic technology that reduces high-angle light and minimizes visual glare. The smooth low glare diffuser gives each luminaire a soft cutoff without visible color separation.

Glare Control Diffuser



2.4mm Hex Pattern

Viewing Angle



0°

45°

>65°


5.5" ROUND DOWNLIGHT 10W TITANIUM LED SERIES



DUAL INSTALLATION


4" J-BOX FLUSHMOUNT

For all models



ACCESSORIES INCLUDED:

- Attach mounting bracket to J-box
- Click downlight into mounting bracket



Mounting Bracket



J-Box Screws




Wire Nuts



LED Adapter

4" & 6" CAN RECESSED

4" CAN - 5.5" & 7" models
6" CAN - 7" model only



ACCESSORIES SOLD SEPARATELY:

- Connect E26 adapter to the LED adapter
- Insert mounting clips and push downlight up until flush with ceiling



E26 Adapter



Mounting Clips



Ground Screw



LED Adapter

SPECIFICATIONS

| Product Model | 58260 10SMPR5.5DIM/927 | 58261 10SMPR5.5DIM/930 | 58262 10SMPR5.5DIM/940 |
|-----------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Type | 5.5" SMPR | 5.5" SMPR | 5.5" SMPR |
| Base | LED Adapter (E26 & GU24 optional) | LED Adapter (E26 & GU24 optional) | LED Adapter (E26 & GU24 optional) |
| Power (W) | 10 | 10 | 10 |
| Voltage - Frequency | 120V 60Hz | 120V 60Hz | 120V 60Hz |
| Color Temp. (ANSI) | Soft White 2700K | Warm White 3000K | Cool White 4000K |
| CRI (Ra) | 90 | 90 | 90 |
| Typical lumens (lm) | 550 | 550 | 560 |
| Efficacy (LPW) | 55 | 55 | 56 |
| Beam Angle | 100° | 100° | 100° |
| Dimmable | Yes** | Yes** | Yes** |
| Housing Compatibility | 4" J-box / Most 6" housing | 4" J-box / Most 6" housing | 4" J-box / Most 6" housing |
| Power Factor | 0.9 | 0.9 | 0.9 |
| Rated Lifetime - L70 (hrs.) | 50,000 | 50,000 | 50,000 |
| Dia. x MOL | 5.59"x1.65" (142x42mm) | 5.59"x1.65" (142x42mm) | 5.59"x1.65" (142x42mm) |
| Weight (lb. / g) | 0.55lb. / 249g | 0.55lb. / 249g | 0.55lb. / 249g |

ACCESSORY ORDERING INFORMATION

| Model | Product | Description |
|---------|---------|--------------------------------------------------------------------------------------------------------------------------|
| SMP/ACC | 58033 | 4" or 6" Recessed Can Accessories for 5.5" & 7" Round & Square (5.5" for Use in 4" Can Only, 7" for Use in 4" or 6" Can) |

* Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$4 incandescent with 1000-hr lifetime, \$30 LED with 50,000-hr lifetime

** List of tested dimmer switches available on website