

# 7" SQUARE DOWNLIGHT 15W TITANIUM LED SERIES



CRISP



15W REPLACES



75W Inc.

80% Energy Savings

\$197 Savings per lamp\*

- ⌚ Innovative CLICK design
- ⌚ SootheOptic low glare technology
- ⌚ Fits most 4" J-boxes and 4" & 6" recessed housings
- ⌚ Installs in just minutes - no rewiring
- ⌚ Wet location rated
- ⌚ Exceptional color rendering CRI 90



50,000 H



DIMMABLE



LOW GLARE



5 YR WARRANTY



CRI (Ra)



WET LOCATION



LM 79

LM 80


TM 21



## DOWNLIGHT PRODUCT FEATURES

### Edge Lighting Technology

The CLICK DESIGN SURFACE MOUNT SQUARE & ROUND DOWNLIGHTS use the latest in edge lighting technology to produce a smooth uniform lighting effect. These naturally low glare downlights integrate seamlessly into all ceiling applications.




- BACK PLATE
- WATERPROOF FOAM
- EDGE LIGHTING REFLECTOR
- LIGHT GUIDE PLATE
- SootheOptic LOW GLARE
- TRIM

### SootheOptic Low Glare Technology

These downlights all feature SootheOptic technology that reduces high-angle light and minimizes visual glare. The smooth low glare diffuser gives each luminaire a soft cutoff without visible color separation.

#### Glare Control Diffuser



2.4mm Hex Pattern

#### Viewing Angle



0°


45°

>65°

## DUAL INSTALLATION


### 4" J-BOX FLUSHMOUNT

For all models



ACCESSORIES INCLUDED:

- Attach mounting bracket to J-box
- Click downlight into mounting bracket



Mounting Bracket



J-Box Screws




Wire Nuts



LED Adapter

### 4" & 6" CAN RECESSED

4" CAN - 5.5" & 7" models  
6" CAN - 7" model only



ACCESSORIES SOLD SEPARATELY:

- Connect E26 adapter to the LED adapter
- Insert mounting clips and push downlight up until flush with ceiling



E26 Adapter



Mounting Clips



Ground Screw



LED Adapter

## SPECIFICATIONS

Product Model	58244 15SMPS7DIM/927	58245 15SMPS7DIM/930	58246 15SMPS7DIM/940
Type	7" SMPS	7" SMPS	7" SMPS
Base	LED Adapter (E26 & GU24 optional)	LED Adapter (E26 & GU24 optional)	LED Adapter (E26 & GU24 optional)
Power (W)	15	15	15
Voltage - Frequency	120V 60Hz	120V 60Hz	120V 60Hz
Color Temp. (ANSI)	Soft White 2700K	Warm White 3000K	Cool White 4000K
CRI (Ra)	90	90	90
Typical lumens (lm)	850	850	870
Efficacy (LPW)	57	57	58
Beam Angle	100°	100°	100°
Dimmable	Yes*	Yes**	Yes**
Housing Compatibility	4" J-box / Most 4" & 6" housing	4" J-box / Most 4" & 6" housing	4" J-box / Most 4" & 6" housing
Power Factor	0.9	0.9	0.9
Rated Lifetime - L70 (hrs.)	50,000	50,000	50,000
Dia. x MOL	7.17"x1.65" (182x42mm)	7.17"x1.65" (182x42mm)	7.17"x1.65" (182x42mm)
Weight (lb. / g)	1.01lb. / 458g	1.01lb. / 458g	1.01lb. / 458g

## ACCESSORY ORDERING INFORMATION

Model	Product	Description
SMP/ACC	58033	4" or 6" Recessed Can Accessories for 5.5" & 7" Round & Square (5.5" for Use in 4" Can Only, 7" for Use in 4" or 6" Can)

\* Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$4 incandescent with 1000-hr lifetime, \$35 LED with 50,000-hr lifetime

\*\* List of tested dimmer switches available on website