

PRO

PAR30SN

LSPro LED PAR30 Short Neck Lamp

Perfect Light Source for Commercial and Residential Applications



PRECISE LED BINNING PROCESS

Detailed and precise LED binning process for concise color output and consistant temperature

90+ CRI FOR EXCEPTIONAL COLOR

SPECIALIZED OPTIC DESIGN

Creates smooth, even light distribution

RELIABLE, ENERGY EFFICIENT, POWERFUL

The 13W PAR30 Short Neck LED lamp provides you with a crisp, beautifully lit environments, while requiring 80% less power and lasting 40 times longer than traditional incandescent bulbs. Perfect for a variety of commercial and residential applications and featuring 90+ CRI for ideal color rendering, the PAR30SN is dimmable and provides a form easily utilized in a variety of luminaires.



PRECISE LED BINNING

Detailed and precise LED binning process for consistant color output and temperature

SPECIALIZED OPTIC DESIGN

Creates smooth, even light distribution

ENERGY STAR RATED

Energy Star rated for quality you can depend on



ORDERING INFORMATION

FAMILY	PRODUCT	WATTAGE EQUIVALENT	COLOR TEMPERATURE	DISTRIBUTION	VOLTAGE	PACKAGING
LSPRO	PAR30SN	75 WE - 75 WATT EQUIVALENT	W27 - WARM WHITE 2700K	FL - FLOOD	120	BX - BOX
			WW - HALOGEN WHITE 3000K	NFL - NARROW FLOOD		
			NW - COOL WHITE 4000K			
			CW - STARK WHITE 5000K			

example: LSPRO 30 75WE W27 FL 120 BX

PAR30 75WE

SPECIFICATIONS ¹	W27	WW	NW	CW
Color Temperature ²	2700K	3000K	4000K	5000K
Output (Lumens) ³	880 (40°)	938 (40°)	855 (40°)	855 (40°)
CBCP (cd)	1793 (40°)	1915 (40°)	1907 (40°)	2084 (40°)
Power Factor	.97	.97	.97	.97
CRI	92.2	93.1	92.8	91.1
R9	66	70	72	65
Beam Angle	40° - Flood			
Equivalent Source Standard	75 WE			
Input Voltage	120V			
Power Consumption	14W			
Dimmable ⁴	Yes			
Housing	Aluminum			
Base	E26			
Lumen Maintenance ⁵ (L ₇₀)	25,000			
Warranty	5 Year Limited			
Environment	Wet			
Certifications	Energy Star; RoHS; UL Listed			

Dimmer Compatibility List:

Lutron LED - Skylark Contour® C-L, Maestro® C-L MACL-153M, Maestro Wireless® C-L MRF2-6CL, Caséta Wireless® C-L PD-6WCL, Diva® C-L DVCL-153P, Ariadni® C-L AYCL-153P, Lumea® C-L LGCL-153P

Lutron Incand. - Diva® DV-600P

Leviton UNV - SureSlide® 6674, SureSlide® 6672, Decora® Rocker Slide DSM10-1LZ, IllumaTech® Slide IPL06-10Z

Leviton ELV - Decora® Rocker Slide DSE06-10Z

Eaton-Copper LED - Aspire 9573

Eaton-Copper Incand. - Aspire 9530

Legrand Pass & Seymour UNV - Harmony® Tru-Unv H703PTUW

¹ Specifications and values supplied are nominal and are subject to change without notification

² Color temperatures conform to nominal CCTs as defined in ANSI Chromaticity Standard C78.377A

³ Lumen measurement complies with IES LM-79-08 testing procedures

⁴ Please consult with Lighting Science Group for a list of compatible dimmers

⁵ Lumen maintenance calculations are based on measurements that comply with IES LM-80-08 testing procedures. L70 = 70% lumen maintenance, or when lamp reaches 70% of initial output