

LED WALL PACKS



FEATURES

- System Light Efficacy 90 LPW
- Easy Installation & Maintenance
- IP65
- Five Years Warranty
- ETL, DLC(4000K Only)
- Optional Shade Included for Field Installation



50% ENERGY EFFICIENCY & LONG LIFE
60% MORE ENERGY EFFICIENT THAN STANDARD HID LAMPS
TYPICAL PAYBACK OF 1 - 3 YEARS

| SKU # | Kelvin | Lumens | CRI | Wattage | Voltage | DLC? | Mounting | Life Hours | Warranty |
|-----------|--------|--------|-----|---------|---------|------|----------|------------|----------|
| PLT-10834 | 4000 | 3600 | 80 | 40 | 120-277 | YES | WALL | 54000 | 5 years |

ADDITIONAL PHOTOS



FEATURES

- Easy Installation & Maintenance
- System Light Efficacy 90 LPW
- Optional Shade Included for Field Installation

TYPICAL APPLICATIONS

- Security Lighting
- Pedestrian Lighting

WARRANTY

WARRANTY **5 Years**

SPECIFICATIONS

PERFORMANCE

3600 Lumen Output (IES)
 40W Power Consumption
 90lm/W Efficacy (IES)
 4000K Color Temperature
 ≥80 CRI
 L70>54,000 hours Lumen Maintenance
 100-277 VAC Input Voltage
 0.95 minimum Power Factor

ENVIRONMENTAL


IP65 IP Rating
 -30 to 45°C Operating Temperature

PHYSICAL


Dimensions (334 x 234 x 297mm)
 Weight 4.7kg
 Wall Mounting Options
 Fixture Material Aluminum Alloy



PHOTOMETRICS



0.0~180.0



Mounting Hight 4m, 0 Tilt,
 50LUX-5LUX

Illumination

| Height | Light Spot | LUX |
|--------|------------|---------|
| 2m | 0.5×3.2m | 142LUX |
| 4m | 0.9×6.4m | 35.5LUX |
| 6m | 1.4×9.6m | 15.8LUX |
| 8m | 1.8×12.8m | 8.9LUX |
| 10m | 2.3×16.1m | 5.7LUX |