

Model: 15T5HE/4F/xxx/DIR/R

Where xxx means 824-965 which indicates CRI and color temperature



ELECTRONIC BALLAST COMPATIBILITY

Series	Model	Load	Compatibility	
			(Ballasts are compatible with 120V & 277V unless otherwise noted)	
			1 Lamp	2 Lamps
GE - UltraMax	GE228MVPSH-A	PS	OK	OK
GE - UltraMax	GE228MVPS-MC	PS	OK	OK
Osram	QHE 2X28UNV PSN-SC	PS	OK	OK
Philips - Advance	ICN-2S28-N	PS	OK	OK
Philips - Advance	ICN-2S28-T	PS	OK	OK
Philips - Advance	IOP-2S28-95-SC-SD	PS	X	X
Philips - Advance	IOP-2S28-115-SC-SD	PS	X	X
Robertson	PSA228T5MV	PS	OK	OK
Robertson	REU128T5120	PS	120V only	—
Universal	B228PUNV-C	PS	OK	OK
Sola	E-725-U-228-R1-S	PS	OK	OK

*GREEN CREATIVE has provided this dimmer compatibility chart for guidance when selecting a ballast, dimmer and lamp combination. Lamps were tested for compatibility with the above listed ballasts and dimmers. Ballasts and dimmers that do not appear on the chart might still be compatible but have not been tested. All testing has been performed with a stable main supply. The quality of the local main, existing installation and wiring, as well as different manufacturer versions of the above ballasts may affect lamp performance. Since no assurance can be provided regarding these factors, it is a general recommendation to perform a test on-site prior to installing the LED lamps.