



LED T8 | BYPASS REPLACEMENT



PRODUCT FEATURES

- Simple Retrofit Installation
- Universal Input Voltage - 120-277V
- Full Glass Lens with 240 Degree Light Distribution
- High Efficacy 100 lm/w Performance
- DLC Qualified
- UL Classified
- ETL Sanitation Listed for Food Service Application
- 5-Year Warranty

\$115 Total Life Savings²

APPLICATIONS

- Office Buildings/Schools
- Warehouse
- Manufacturing Facilities
- Parking Garages

Model Number	Lamp Type	Base	Watts / Replaced	Lumens	CCT ¹	MOL	Light Distribution	Certification	Warranty
LBP8F1050A	Bypass	G13	9W / 17W	1000 lm	5000K	24"	240°	UL/DLC	5-Years
LBP8F1750A	Bypass	G13	15W / 32W	1650 lm	5000K	48"	240°	UL/DLC	5-Years
LBP8F2050A	Bypass	G13	18W / 32W	2000 lm	5000K	48"	240°	UL/DLC	5-Years

NOTE 1: Alternate 3500K and 4100K Color Temperatures available

NOTE 2: Savings calculated by 50,000 hour Lifetime, Electricity rated \$0.12, and 3 Operating Hours Per Day

