

LED Omni-directional A19



Ordering Information

| Model No. | Item name | Lumens ² (lm) | Watts (w) | CCT ¹ (k) | Efficacy (lm/w) | CRI | Lifetime ³ (h) | Beam Angle | Base type | Voltage (v) | Weight (lb) | Cerification | Equivalent ⁴ (w) |
|--------------------|-----------|-----------------------------|--------------|-------------------------|--------------------|-----|------------------------------|---------------|--------------|----------------|----------------|-----------------------------------|--------------------------------|
| G-L6-A19D-9W-2700K | A19 | 800 | 9 | 2700 | 89 | 80 | 25000 | >300° | GU24 | 120 | 0.37 | UL, FCC, Energy Star ⁵ | 60 |

3 THREE YEARS WARRANTY



1. CCT Range complies to ANSI C78.377-2008.

2. Thermally stable typical lumens ($\pm 10\%$)

3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.

4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.


5. Energy Star® will be available in May, 2013.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.

Note: All lamps meet Energy Star® Integral LED Lamp requirements, and will be submitted for testing.

Dimensions

| Model | MOL | Diameter |
|------------|--------------|--------------|
| A19 | 4.41" | 2.50" |



Note: Lamp shape conforms to ANSI C78.21-2003.

Note: Designed to comply with RoHS Directive 2002/95/EC.

Energy Savings

| Model No. | Equivalent | Energy Savings |
|--------------------|------------------|----------------|
| G-L6-A19D-9W-2700K | 60W Incandescent | \$135 |

*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh. Does not include maintenance and replacement lamp savings.