

PLT-20026 LED HORIZON HIGH BAY™ 4L

LED READY FIXTURE

TECHNICAL DATA SHEET

FEATURES

- Use 30% less energy than a traditional fluorescent fixture
- Iron phosphate pre-treatment for maximum adhesion and rust resistance
- Sufficient knockouts are available for electrical and sensor connection
- · LED ready with non-shunted sockets
- Excellent industrial light source for task lighting and illuminating areas with low to medium ceiling height


APPLICATION


Larger warehouses, retail applications, commercial buildings, and work areas.

PRODUCT DETAILS

ELECTRICAL	
Lamp Type (not included)	T8
Number of Lamps	4
Voltage	No Ballast
CONSTRUCTION	
Housing	22 Gauge C.R.S
Reflector	86% MIRO4 Aluminum
Base / Power Supply	Hard Wired
Finish	High Gloss Baked Enamel
ENVIRONMENT	
Operating Temperature (fixture only)*	-20°C ~ 50°C
Suitable Location	DAMP
Ingress Protection Rating	IP40
LIFESPAN	
Warranty	3
CERTIFICATIONS	
N/A	

PACKAGING	
Master Carton	1pc / 811768025293
Country of Origin	China
HS Tariff	9405.10.6020
DIMENSIONS	
Dimensions (Inches)	48"(L) x 11.8"(W) x 3.7"(H)
	48"





ORDERING

ITEM# DES	CRIPTION	CASE
PLT-20026	LED HORIZON HIGH BAY™ FOR 4 T8 - SUPERIOR LIFE®	1
ACCESSORIES	7 / REPLACEMENT PARTS	
PLT-54900	HIGH BAY/LOW BAY PASSIVE INFRARED OCCUPANCY SENSOR	50

^{*} Operating temperature may vary depending on the lamps used.