


TRACK 8W S

Preliminary Specifications



PRO



- 625 lumen output 8W replaces 75W PAR30 halogen
- High efficacy 71 LPW in Warm White
- Sleek design, integrated driver
- 350° horizontal and 90° vertical adjustment
- Smooth face MirOptic lens



COMPATIBLE WITH H, J & L TRACK TYPE



TRACK 8W S

Preliminary Specifications



Ref.#:DS045-TRS-8W

SPECIFICATIONS*

Product	8TRSG4DIM/827NF30/ / _	8TRSG4DIM/830NF30/ / _	8TRSG4DIM/840NF30/ / _ (MTO)
Track Type	H/J/L (L-MTO)	H/J/L (L-MTO)	H/J/L (L-MTO)
Power (W)	8.8	8.8	8.8
Voltage - Frequency	120V 60Hz	120V 60Hz	120V 60Hz
Color Temp. (ANSI)	Warm White 2700K	Warm White 3000K	Natural White 4000K
CRI (Ra) (typ.)	80	80	80
Typical lumens (lm)	600	625	650
Efficacy (LPW)	68	71	74
Beam Angle	NF 30°	NF 30°	NF 30°
CBCP (cd)	1905	1950	2000
Dimmable	Yes	Yes	Yes
Power Factor	0.9	0.9	0.9
Rated Lifetime - L70 (hrs.)	40,000	40,000	40,000
H x L x Dia.	6.1"x3.46"x2.76" (155x88x70mm)	6.1"x3.46"x2.76" (155x88x70mm)	6.1"x3.46"x2.76" (155x88x70mm)
Weight (lb. / g)	0.56lb / 255g	0.56lb / 255g	0.56lb / 255g
Finish	White / Black	White / Black	White / Black

ORDERING INFORMATION

Model	Finish	Track Type
8TRSG4DIM/827NF30/	W-White	H-Halo
	B-Black	J-Juno
		L-Lightolier
Example: 8TRSG4DIM/827NF30/W/J		

* Specification data is preliminary and may be subject to change