

# Dimmable CFL & LED bulbs

**Compatible with Lutron 100W & 150W C-L® dimmers**



# Dimmable CFL & LED bulbs

## Compatible with C·L<sup>®</sup> dimmers

List updated March 18, 2016

This list is designed to help you select bulbs that are compatible with Lutron C·L dimmers. The CFL and LED bulbs on this list were extensively tested by Lutron; the Lutron C·L dimmers were evaluated by UL and meet applicable safety standards.

## How to use this list

If you already have a bulb:

Use the “Find” tool in your browser or PDF viewer to search for the model number that’s printed on the bulb. Then choose a C·L dimmer that’s compatible with that bulb.

If you already have a C·L dimmer:

Use the table of contents to find the corresponding pages for that control, and then select a bulb from that list.

## What does “compatible” mean?

Compatible means that the bulbs can be dimmed, although the bulb’s dimming performance may not match what you’re used to seeing when dimming an incandescent or halogen bulb. These bulbs have also been electrically tested to confirm that the control may be used up to its full rated CFL/LED load without affecting the life of the control.

Products on this list are considered compatible with the respective Lutron C·L dimmers. Depending on the quality of the bulb you select, compatible bulbs may still:

- have less dimming range than an incandescent or halogen bulb
- dim less smoothly than an incandescent or halogen bulb
- flicker or shimmer at certain light levels
- buzz

# Dimmable CFL & LED bulbs

## Compatible with C·L® dimmers

List updated March 18, 2016

Warranty on your Lutron 150W C·L dimmer will be void if used with bulbs that are not on this Lutron compatible bulb list.

Please note: Bulb variations in lamp design and construction affect performance. Bulb manufacturers can modify their bulbs at any time, without notice to Lutron. This prevents Lutron from ensuring ongoing compatibility. For up-to-date specifications, performance, and/or any related recall information about the bulb, please visit the bulb manufacturer's website.

*This document provides information from manufacturers who are not Lutron agents or affiliates. The listing of a manufacturer or the existence of any external link to another website does not suggest that Lutron is endorsing the linked company, its products and/or its services. Purchasers should ask appropriate questions and request references before buying any products and/or entering a contract with any party. The information contained in this document is intended for illustrative and comparative purposes only, and is subject to change at any time. Lutron does not warrant that (a) the list of manufacturers is all-inclusive; (b) the information is complete, up-to-date, accurate and/or error-free; (c) the products and Lutron controls listed will always be compatible; and (d) that the information provided will be a viable or appropriate solution for your project needs. You are entirely responsible for and assume all risk for the use of the information.*

# Dimmable CFL & LED bulbs

Compatible with C•L® dimmers

List Updated March 18, 2016



## LED bulbs for Maestro® C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Cree	6W	BA19-04527OMB-12DE26-3_1	A19 4Flow, 83CRI, 2700K, 460 Lumen, E26
	6W	BA19-04527OMF-12DE26-1U100	A19, Warm Soft White, 2700K, 450 Lumen, Medium base
	6W	BA19-04527OMF-12DE26-2U100	A19, Warm Soft White, 2700K, 450 Lumen, Medium base
	6W	BA19-04527OMF-12DE26-3U100	A19 4Flow, 2700K, 460 Lumen, E26
	6W	BA19-04550OMB-12DE26-3_1	A19 4Flow, 83CRI, 5000K, 460 Lumen, E26
	6W	BA19-04550OMF-12DE26-2U500	A19, 5000K, 450 Lumen, 40WE, 4pk
	6W	BA19-04550OMF-12DE26-3U100	A19 4Flow, 5000K, 460 Lumen, E26
	9.5W	BA19-08027OMF-12DE26-2U100	A19, Soft White, 2700K, 800 Lumen, Medium base
	9.5W	BA19-08027OMF-12DE26-2U500	A19, 2700K, 800 Lumen, E26, 60WE, 4pk
	9.5W	BBR30-06527FLF-12DE26-1U100	BR30, 650 Lumen, Soft White, 2700K
	9.5W	BBR30-06550FLF-12DE26-1U100	BR30, Daylight, 5000K 650 Lumen, 9.5W
	9.5W	BBR40-07627FLF-12DE26-1U_00	BR40, 2700K, 760 Lumen, Flood
	9.5W	BBR40-07650FLF-12DE26-1U10	BR40, 5000K, 760 Lumen, Flood
	10W	BA19-08027OMB-12DE26-3_1	A19, 4Flow, 2700K, 815 Lumen, E26, 83 CRI
	10W	BA19-08050OMB-12DE26-3_1	A19, 4Flow, 5000K, 815 Lumen, E26, 83 CRI
	10.5W	BPAR30S-0853040C-12DE26-1C100	PAR30S, 3000K, 850 Lumen, 40° Flood
	11.5W	DRDL4-05727009-12DE26-1C100	4" Downlight, 2700K TW, 575 Lumen, E26 retrofit
	12.5W	DRDL6-06227009-12DE26-1C100	6" Downlight, 2700K TW, 625 Lumen, E26 retrofit
	12.5W	DRDL6-06250009-12DE26-1C100	6" Downlight, 5000K TW, 625 Lumen, E26 retrofit
	15W	DRDL6-11027009-12DE26-1C100	6" Downlight, 2700K, 1100 Lumen
16.5W	BPAR38-1503027T-12DE26-2U_00	PAR38, 3000K, 1510Lm, E26, Spot	
16.5W	BPAR38-1503047T-12DE26-2U_00	PAR38, 3000K, 1510Lm, E26, Flood	
18W	BA21-16027OMF-12DE26-1U100	A21, 2700K, 1600 Lumen, E26, 18W	
18W	BA21-16050OMF-12DE26-1U100	A21, 5000K, 1600 Lumen, E26, 18W	
Duracell	6W	LED110342B	A19, 450 Lumen, E26, 40WE
	6W	LED11340B	A19, 3000K, 450 Lumen, E26, 40WE
	6W	LED11341B	A19, 450 Lumen, E26, 40WE
EcoSmart	5W	5020001XXYY	Candle, 2700K, 350 Lumens
	5.5W	5bHPR500STW1D18	PAR20, 3000K 450Lm, E26
	5.5W	5bHPR500STW1D19	PAR20, 5000K 470Lm, E26
	6W	ECS 25 40WE W27 120 DG	G25, 2700K, 400 Lumen, E12
	6W	ECS GP19 WW 40WE 120†	A19, 3000K
	6.5W	50217013006	PAR20, 3000K, 450 Lumens
	7W	ECS 25 60WE W27 120 DG	G25, 2700K, E12
	7W	ECS BR20 50WE CW 120 G1 BL	BR20, Daylight, 5000K, 525 Lumen, E26
	7.5W	BPA15/CL/500/LED/ESM	A15, Soft White, 2700K, 500 Lumen, E26
	7.5W	BPA15C/CL500/LED/ESM	A15, Soft White, 2700K, 500 Lumen, E12
	7.5W	BPCFC/500/LED/ESM	B10, Soft White, 2700K, 500 Lumen, E12
	7.5W	BPEFC/500/LED/ESM	B10, Soft White, 2700K, 500 Lumen, E26
	7.5W	BPGM/CL/500/LED/ESM	G16.5, Soft White, 2700K, 500 Lumen, E26
	8W	ECS 20 50WE CW FL 120 TP	PAR20, Daylight, 5000K, 575 Lumen, E26
	8W	ECS 20 50WE WW FL 120 TP	PAR20, Bright White, 3000K, 500 Lumen, E26
	8W	ECS 20 CW FL 50WE 120	PAR20, 5000K, 490 Lumen
	8W	ECS 20 WW FL 50WE 120	PAR20, 3000K, 450 Lumen
	8W	ECS BR20 50WE CW 120 DG	BR20, Daylight, 5000K, 600 Lumen, E26
	8W	ECS BR20 50WE W27 120	BR20, Soft White, 2700K
	8W	ECS BR20 50WE WW 120 DG	BR20, Warm White, 3000K, 550 Lumen, E26
9W	5bSA800STQ1D02	A19, 3000K, 800Lm, E26, 4pk	
9W	A810SS-Q1D-01 (5bSA800STQ1D01)	A19, 2700K, 800Lm, E26	
9W	A810SS-Q1D-04 (5bSA800STQ1D03)	A19, 5000K, 840Lm, E26, 4pk	
9.5W	5bHPR650STW1D29	PAR30, 3000K, 650Lm, E26	
9.5W	5bHPR650STW1D30	PAR30, 3000K, 680Lm, E26	
9.5W	ECS DN4 CW E26 120	4" Downlight, Daylight, 5000K, 650 Lumen, E26, retrofit	
9.5W	ECS DN4 CW GU24 120	4" Downlight, Daylight, 5000K, 650 Lumen, Gu24 base, retrofit	

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K

# Dimmable CFL & LED bulbs

Compatible with C•L® dimmers

List Updated March 18, 2016



## LED bulbs for Maestro® C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
EcoSmart	9.5W	ECS DN4 W27 E26 120	4" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit
	9.5W	ECS DN4 W27 GU24 120	4" Downlight, Soft White, 2700K, 650 Lumen, GU24 base, retrofit
	9.5W	ECS DN6 CW GU24 120	6" Downlight, Daylight, 5000K, 650 Lumen, Gu24 base, retrofit
	9.5W	ECS DN6 W27 E26 120	6" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit
	9.5W	ECS DN6 W27 E26 120 2BX	6" Downlight, Soft White, 2700K, E26 retrofit, 2pk
	9.5W	ECS DN6 W27 E26 120 BX V3	6" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit
	9.5W	ECS DN6 W27 GU24 120	6" Downlight, Soft White, 2700K, 650 Lumen, GU24 base, retrofit
	10W	DL-N14A10FR1-27	5/6" Downlight, 2700K, 650Lm, E26
	10W	DL-N14A10FR1-50	5/6" Downlight, 5000K, 650Lm, E26
	10W	DL-N14A10FR2-27	5/6" Downlight, 2700K, 650Lm, GU24
	10W	DL-N14A10FR2-50	5/6" Downlight, 5000K, 650Lm, GU24
	10W	ECS BR30 65WE CW 120 DG†	BR30, Daylight, 5000K, 700 Lumen, E26
	10W	ECS BR30 65WE CW 120 DG 3PK†	BR30, Daylight, 5000K, 700 Lumen, E26, 3pk
	10W	ECS BR30 65WE W27 120 DG†	BR30, Soft White, 2700K, 650 Lumen, E26
	10W	ECS BR30 65WE W27 120 DG 3BX†	BR30, Soft White, 2700K, 650 Lumen, E26, 3pk
	10W	ECS BR30 65WE WW 120 DG†	BR30, Warm White, 3000K, 650 Lumen, E26
	10.5W	ECS 30 75WE WW GB FL 120	PAR30 Gimbal, 3000K, 750 Lumen, E26, 75WE
	10.5W	ECS 30 75WE xxx GB xx 120	PAR30 Gimbal, Various color temperatures, 75WE
	11W	5020901XXYY†	BR30, 2700K, 770 Lumens
	11.5W	ECS BR30 65WE CW 120†	BR30, 5000K, Medium Base
	11.5W	ECS BR30 65WE W27 120†	BR30, 2700K, 650 Lumen, Medium Base
	12W	ECS A19 CW 60WE 120	A19, 5000K, 850 Lumen
	12W	ECS A19 WW 60WE 120	A19, 3000K, 800 Lumen
	13W	5bHPR1000SW1D19	PAR38, 3000K, 900Lm, E26
	13W	5bHPR1000SW1D20	PAR38, 5000K, 1000Lm, E26
	13W	ECS 30 CW FL 75WE 120	PAR30, 5000K, 810 Lumen
	13W	ECS 30 WW FL 75WE 120	PAR30, 3000K, 750 Lumen
	14W	ECS BR40 90WE CW 120 DG	BR40, Daylight, 5000K, 1050 Lumen, E26
	14W	ECS BR40 90WE W27 120 DG	BR40, 2700K, 1000 Lumen, E26
	15W	ECS 38 CW FL 90WE 120	PAR38, 5000K, 970 Lumen
	15W	ECS 38 WW FL 90WE 120	PAR38, 3000K, 900 Lumen
	15W	ECS BR40 90WE W27 120	BR40, Soft White, 2700K
	Feit	4.5W	R14DM/LED
4.8W		CFCDM/300/LED†	Candle, 3000K, 310 Lumen, Candelabra Base
4.8W		EFCDM/300/LED†	Candle, 3000K, 310 Lumen, Medium Base
4.9W		BPCEFC/927/LED/3	Candle, 2700K, 330 Lumen, E12
6.5W		BPMP16/GU10/DM/LED	MR16, GU10 base
6.5W		MR16/GU10/DM/LED	MR16, GU10 base
6.5W		R16DM/LED	R16, Soft White, 2700K, 400 Lumen, E26, 40WE
8W		A19/DM/GU24/LED	A19, 3000K, GU24 Base
8W		A19/DM/LED	A19, 3000K
8W		A19/DM/LED/CAN	A19
8W		A19/DM/LED/RP/CAN	A19
8W		A19DM/5K/LED	A19, 5000K
8W		BPCEA19/DM/LED	A19
8W		BPCEG25/927/LED/3	G25, 2700K, 495 Lumen, E26
8W		BPCER20/DM/LED†	R20 (90mA ridged reflector version)
8W		R20/DM/LED†	R20, 2700K, 450 Lumen (90mA ridged reflector version)
8W		R20DM/LED/CAN†	R20 (90mA ridged reflector version)
8.5W		BR30M65/LED/6	R30, 650 Lumen, E26
9.5W		BPCER20/DM/LED	PAR20
9.5W		PAR20/5K/LEDG5	PAR20, 5000K
9.5W		PAR20/5K/LEDG5/CAN	PAR20, 5000K

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K

# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Maestro<sup>®</sup> C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
	9.5W	PAR20/LEDG5	PAR20, 3000K, 450 Lumen
	9.5W	PAR20/LEDG5/CAN	PAR20
	9.7W	CELEDRT4/927	4" Downlight, 2700K, 520 Lumen, E26
	9.7W	EDRT4/927	4" Downlight, 2700K, 520 Lumen, E26
	9.7W	LEDR4/827	4" Downlight, 2700K, 520 Lumen, E26
	9.7W	LEDR4/830	4" Downlight, 3000K, 520 Lumen, E26
	9.7W	LEDR4/850	4" Downlight, 5000K, 520 Lumen, E26
	9.7W	LEDRT4/927	4" Downlight, 2700K, 520 Lumen, E26
	9.7W	LEDRT4/940	4" Downlight, 4000K, 520 Lumen, E26
	10W	BPAG800/5K/LED	A19, 5000K
	10W	BPAG800/LED	A19, 3000K, 800 Lumen
	13W	BPCEBR30LED	BR30
	13.5W	A19/OM800/5K/LED	A19, 5000K, Omni Directional
	13.5W	A19/OM800/LED	A19, 3000K, Omni Directional
	13.5W	BPCEA19/OM800/LED	A19, Omni Directional
	13.5W	BPCEA19/OM800/LED/CAN	A19, Omni Directional
	14W	LEDR56/830	Downlight, 3000K, 925 Lumen, retrofit kit
	15W	BPCEPAR30/LEDG5	PAR30
	15W	PAR30L/5K/LEDG5	PAR30, 5000K
	15W	PAR30L/5K/LEDG5/CAN	PAR30, 5000K
	15W	PAR30L/LEDG5	PAR30
	15W	PAR30L/LEDG5/CAN	PAR30
	16W	A19/OM1100R/LED	A19, 3000K, 1100 Lumen, Omni Directional
	16.8W	LEDR56/3K	5" or 6" Downlight, 3000K, 840 Lumen
	17W	BPCEBR40/LED	BR40, 2700K, 1065 Lumen
	17W	BR40/DM/LED†	BR40, 2700K, 1065 Lumen
	18W	18PAR38/DM/LED	PAR38, 3000K
	20W	20PAR38/LEDG5	PAR38
	20W	BPCEPAR38/LEDG5	PAR38
	20W	PAR38/5K/LEDG5	PAR38, 5000K
	20W	PAR38/5K/LEDG5/CAN	PAR38, 5000K
	20W	PAR38/LEDG5	PAR38
	20W	PAR38/LEDG5/CAN	PAR38
	21.5W	CELEDRT56/927/2	5/6" Downlight, 2700K, 1250 Lumen, E26
	21.5W	LEDR56/827	5/6" Downlight, 2700K, 1250 Lumen, E26
	21.5W	LEDR56/927/MP/4	5/6" Downlight, 2700K, 1250 Lumen, E26, 4 pack
	21.5W	LEDR56HO/830	5/6" Downlight, 3000K, 1250 Lumen, E26
	21.5W	LEDR56HO/850	5/6" Downlight, 5000K, 1250 Lumen, E26
	22W	A/OM1600R/27K/LED	A21, 2700K, 1600 Lumen
	22W	A/OM1600R/5K/LED	A21, Daylight, 5000K, 1600 Lumen
	22W	A/OM1600R/LED	A21, Warm White, 3000K, 1600 Lumen
	8W	LED8DA19/827	A19, 2700K, 450 Lumen, E26
	10.5W	FAM45LED11DAV3H	A19, 2700K, 800 Lumens, E26, 2pk
	11W	LED11DA19RVL/TP	A19, 2700K, 570 Lumen
	11W	LED11DA19V2	A19, 2700K, 800 Lumen
	12W	LED12DR30RVL/BK	BR30, Reveal
	12W	LED12DR30RVL/CDN	BR30, Reveal
	12W	LED12DR30RVL/TP	BR30, Reveal 2850K, 630 Lumen
	12W	LED12RS4RVLE26PB (95390)	Downlight, 2700K, 630 Lumen, E26
	12W	LED12RS4RVLGUPB (95391)	Downlight, 2700K, 630 Lumen, GU24
	12W	LED12RS6RVL326PB (95392)	Downlight, 2700K, 630 Lumen, E26
	12W	LED12RS6RVLGUPB (95393)	Downlight, 2700K, 630 Lumen, GU24
	18W	LED18D38W827/15	PAR38, 2700K, E26, 15° Beam
	18W	LED18D38W827/25	PAR38, 2700K, E26, 25° Beam
	18W	LED18D38W827/40	PAR38, 2700K, E26, 40° Beam
	18W	LED18D38W830/15	PAR38, 3000K, 1400 Lumen, E26, 15° Beam
	18W	LED18D38W830/25	PAR38, 3000K, 1400 Lumen, E26, 25° Beam

Feit

GE

† Requires a minimum of 2 lamps  
 †† Requires a minimum of 3 lamps  
 © Lutron Electronics Co., Inc. | PN 368-3266K

# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Maestro<sup>®</sup> C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
GE	18W	LED18D38W830/40	PAR38, 3000K, 1400 Lumen, E26, 40° Beam
	18W	LED18D38W927/15	PAR38, 2700K, 1100 Lumen, E26, 15° Beam
	18W	LED18D38W927/25	PAR38, 2700K, 1100 Lumen, E26, 25° Beam
	18W	LED18D38W927/40	PAR38, 2700K, 1100 Lumen, E26, 40° Beam
	18W	LED18D38W930/15	PAR38, 3000K, 1200 Lumen, E26, 15° Beam
	18W	LED18D38W930/25	PAR38, 3000K, 1200 Lumen, E26, 25° Beam
	18W	LED18D38W930/40	PAR38, 3000K, 1200 Lumen, E26, 40° Beam
Halco	20W	PAR38FL20/827/LED	PAR38, 2700K, 1150 Lumen Flood
	20W	PAR38FL20/830/LED	PAR38, 3000K, 1200 Lumen Flood
	20W	PAR38FL20/840/LED	PAR38, 4000K, 1250 Lumen Flood
	20W	PAR38FL20/850/LED	PAR38, 5000K, 1300 Lumen Flood
	20W	PAR38NFL20/827/LED	PAR38, 2700K, 1150 Lumen Flood
	20W	PAR38NFL20/830/LED	PAR38, 3000K, 1200 Lumen Flood
	20W	PAR38NFL20/840/LED	PAR38, 4000K Flood
	20W	PAR38NFL20/850/LED	PAR38, 5000K, 1300 Lumen Flood
	20W	PAR38SP20/827/LED	PAR38, 2700K, 1150 Lumen Spot
	20W	PAR38SP20/830/LED	PAR38, 3000K, 1200 Lumen Spot
	20W	PAR38SP20/840/LED	PAR38, 4000K Spot
	20W	PAR38SP20/850/LED	PAR38, 5000K, 1300 Lumen Spot
Halo	14.8W	SLD612827WHUNVJB	6" Downlight, 2700K, 1100 Lumen, E26
	14.8W	SLD612830WHUNVJB	6" Downlight, 3000K, 1150 Lumen, E26
	14.8W	SLD612835WHUNVJB	6" Downlight, 3500K, 1200 Lumen, E26
	14.8W	SLD612840WHUNVJB	6" Downlight, 4000K, 1215 Lumen, E26
	14.8W	SLD612927WHUNVJB	6" Downlight, 2700K, 880 Lumen, E26
	14.8W	SLD612930WHUNVJB	6" Downlight, 3000K, 925 Lumen, E26
	14.8W	SLD612935WHUNVJB	6" Downlight, 3500K, 965 Lumen, E26
Lighting Science	10.5W	LS 30 75WE xxx GB xx 120	PAR30, various color temperatures
	11.5W	DFN BR30 65WE CW 120 <sup>†</sup>	BR30, Cool White, 5000K, Medium base
	11.5W	DFN BR30 65WE NW 120 <sup>†</sup>	BR30, Neutral White, 4000K, Medium base
	11.5W	DFN BR30 65WE W27 120 <sup>†</sup>	BR30, Warm White, 2700K, Medium base
	11.5W	DFN BR30 65WE WW 120 <sup>†</sup>	BR30, Warm White, 3000K, Medium base
Litetronics	13W	LS GLP6 W27 120 WH S1 BX	6" Downlight, 2700K, E26 retrofit
	14W	LP14550FL2D	BR30, 2700K, 925 Lumen
	14W	LP14550FL4D	BR30, 3000K, 925 Lumen
	14W	LP14550FL6D	BR30, 4000K, 925 Lumen
Osram	6W	OSRAM 6W LED A19 270	A19, 2700K, 450 Lumen, E26, 40WE
	6W	OSRAM 6W LED A19 500	A19, 5000K, 450 Lumen, E26, 40WE
	10W	73157-1	5/6" Downlight, 4100K, 700 Lumen, E26
	10W	73159-1	5/6" Downlight, 5000K, 700 Lumen, E26
	10W	73394 (LEDRT56700827FL80)	5/6" Downlight, 2700K, 700 Lumen, E26
	10W	73395-1	5/6" Downlight, 3000K, 700 Lumen, E26
Philips	3.5W	9290002417	Candle, 2700K, 150 Lumen, E12 Candelabra base
	3.5W	9290002419	Candle, 2700K, 150 Lumen, E26 medium base, blunt tip clear
	3.5W	457226 (9290011668)	Candle, 2700K, 180 Lumen, E12, Warm Glow
	3.5W	457234 (9290011668)	Candle, 2700K, 180 Lumen, E12, Warm Glow
	3.5W	457242 (9290011668)	Candle, 2700K, 180 Lumen, E12, Warm Glow
	4.5W	454371	PAR16, 3000K, 315 Lumens
	4.5W	9290002439	Candle, Warm White, 2700K, 320 Lumen, E26 base, Post Light
	4.5W	9290002797 <sup>†</sup>	Candle, 2700K, 330 Lumen, E26, blunt tip
	4.5W	9290002889 <sup>†</sup>	Candle, 2700K, 330 Lumen, E12, blunt tip
	4.5W	9290002890 <sup>†</sup>	A15, 2700K, 330 Lumen, E12
	4.5W	9290002891 <sup>†</sup>	A15, 2700K, 330 Lumen, E26
	4.5W	457119 (9290011673)	Candle, 330Lm, E26
	4.5W	457168 (9290011672)	G16.5, 330 Lm, E26
4.5W	457184 (9290011670)	Candle, 330Lm, E12	

<sup>†</sup> Requires a minimum of 2 lamps

<sup>††</sup> Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K

# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Maestro<sup>®</sup> C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
	6W	9290002242	MR16, 3000K, 300 Lumen, GU10 base
	6W	9290002443	PAR16, 3000K, 300 Lumen, E26
	6W	456995 (9290011557)	R20, 2700K, 450 Lumen, Warm Glow
	6.5W	9290011347 (455741)	A19, Warm Glow, 450 Lumen
	8W	9290002267	A19, 2700K, 470 Lumen
	8W	9290002295	A19, 5000K, 470 Lumen
	8W	9290002329	PAR20, 3000K, 470 Lumen, E26
	8W	9290002330	PAR20
	8W	9290002331	PAR20
	8W	9290002332	PAR20
	8W	9290002333	PAR20
	8W	9290002334	PAR20
	8W	9290002335	PAR20
	8.5W	9290002543	BR30, 5000K, 730 Lumen, 8.5W
	9.5W	455840 (9290011345)	A19, Soft White, 2200-2700K, 800 Lumen, E26
	10W	458828 (9290011816)	A19, 2700K, 800 Lumen, 60WE, E26
	10W	459339 (9290011898)	G25, 2700k, 800 Lumen, E26
	10.5W	9290002544	BR30, 2700K, 730 Lumen
	10.5W	9290002707	A19 SlimStyle, Soft White, 2700K, 800 Lumen, 3pk
	11W	9290002268	A19, 2700K, 830 Lumen
	11W	9290002296	A19, 5000K, 830 Lumen
	11W	9290011113	PAR30L, 3000K, ? Lumen, E26
	12W	9290002580 (431392)	BR40, 2700K, 800 Lumen
	13W	9290011120	A21 SlimStyle, 2700K, 1100 Lumen
	13W	9290002523 13PAR38/F25 3000 DIM AF RO	PAR38, 3000K, 950 Lumen
Philips	14W	459065	A19, 2700K, 1100Lm, 75WE, E26
	14W	9290011839	A21, 2700K, 1100 Lumen, E26
	15W	9290002426	A21, 2700K, 1180 Lumen
	15W	9290002595	A21, Soft White, 2700K, 1180 Lumen, E26
	18W	9290011741	A21, 2700K, 1600Lumen, E26
	18W	459107 (9290011741)	A21, 2700K, 1600 Lumen, E26
	18W	459115 (9290011741)	A21, 2700K, 1600Lumen, E26
	18W	459123 (9290011741)	A21, 2700K, 1600Lumen, E26
	18W	459131 (9290011741)	A21, 2700K, 1600Lumen, E26
	19W	453340	A19, 2700K, 1620Lm, 100WE, E26
	19W	9290002473	PAR38, 3000K, 1250 Lumen
	19W	9290002577 (431395)	PAR38, 1300 Lumen, 25deg flood
	19W	9290002578 (431403)	PAR38, 1300 Lumen, 35deg flood
	19.5W	9290002251	PAR38, 3000K, 1210 Lumen
	19.5W	9290002252	PAR38, 2700K, 1183 Lumen
	19.5W	9290002253	PAR38, 3000K, 1212 Lumen
	19.5W	9290002291	PAR38, 4000K, 1207 Lumen
	19.5W	9290002312	PAR38, 2700K, 1100 Lumen
	19.5W	9290002313	PAR38, 2700K, 1196 Lumen
	19.5W	9290002314	PAR38, 3000K, 1200 Lumen
	19.5W	9290002315	PAR38, 3000K, 1225 Lumen
	19.5W	9290002316	PAR38, 4000K, 1200 Lumen
	19.5W	9290002317	PAR38, 4000K, 1245 Lumen
	19.5W	9290002321	PAR38, 2700K, 1172 Lumen
	19.5W	9290002322	PAR38, 5000K, 1300 Lumen
	22W	9290002290	A21, 2700K, 1780 Lumen, Medium base
Project Source	10W	DLS22-06B30D1E-WH-1	Downlight, 3000K, 650 Lumens, E26
	8W	S8794	A19, 2700K, 450 Lumen, GU10
	8W	S8995	A19, 3000K, 450 Lumen
Satco	9W	S8991	4" Downlight
	11W	S8993-S8994	BR30, 3000K, Medium and GU24 bases
	11W	S9043-S9045	BR30, various color temperatures

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K





# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Maestro<sup>®</sup> C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description	
Satco	11W	S9084	PAR30, 3000K, 780 Lumen, E26, short neck, 25° Beam	
	11W	S9085	PAR30, 4000K, 780 Lumen, E26, short neck, 25° Beam	
	11W	S9086	PAR30, 3000K, 780 Lumen, E26, short neck, 40° Beam	
	11W	S9087	PAR30, 4000K, 780 Lumen, E26, short neck, 40° Beam	
	11W	S9088	PAR30, 3000K, 780 Lumen, E26, long neck, 25° Beam	
	11W	S9089	PAR30, 4000K, 780 Lumen, E26, long neck, 25° Beam	
	11W	S9090	PAR30, 3000K, 780 Lumen, E26, long neck, 40° Beam	
	11W	S9091	PAR30, 4000K, 780 Lumen, E26, long neck, 40° Beam	
	13W	S9003	R40, 3000K, 880 Lumen	
	13W	S9046	R40, 2700K, 850 Lumen	
	13W	S9047	R40, 4000K, 920 Lumen	
	13W	S9048	R40, 5000K, 950 Lumen	
	14W	S8947-S8949	PAR30 Longneck	
	14W	S8971-S8973	PAR30 Longneck	
	15W	S9440	PAR38, 2700k, 1100 Lumen, E26	
	15W	S9445	PAR38, 2700k, 1100 Lumen, E26	
	15W	S9454	PAR38, 2700k, 1100 Lumen, E26	
	17W	S8977-S8979	PAR38	
	17W	S8984-S8986	PAR38	
	17W	S9092	PAR38, 3000K, 1200 Lumen, E26, 25° beam	
	17W	S9093	PAR38, 4000K, 1200 Lumen, E26, 25° beam	
	17W	S9094	PAR38, 3000K, 1200 Lumen, E26, 40° beam	
	17W	S9095	PAR38, 4000K, 1200 Lumen, E26, 40° beam	
	18W	S9455	PAR38, 3000K, 1400 Lumen, E26, Flood	
	18W	S9456	PAR38, 4000K, 1400 Lumen, E26, Flood	
	Solais	7W	LRP20/25/27K	PAR20, 2700K, 475 Lumen, E26, 25° Beam
		7W	LRP20/25/30K	PAR20, 3000K, 500 Lumen, E26, 25° Beam
		7W	LRP20/40/27K	PAR20, 2700K, 475 Lumen, E26, 40° Beam
		7W	LRP20/40/30K	PAR20, 3000K, 500 Lumen, E26, 40° Beam
		11W	LR20/25/27K/675/xx	PAR20, 2700K, 675 Lumen, E26, narrow flood
		11W	LR20/25/30K/750	PAR20, 3000K, 750 Lumen, E26, narrow flood
		11W	LR20/40/27K/675/xx	PAR20, 2700K, 675 Lumen, E26, wide flood
11W		LR20/40/30K/750/xx	PAR20, 3000K, 750 Lumen, E26, wide flood	
16W		LR30/10/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 10° Beam	
16W		LR30/10/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 10° Beam	
16W		LR30/10/30K/1200/xx	PAR30, 3000K, 1200 Lumen, E26, short neck, 10° Beam	
16W		LR30/15/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 15° Beam	
16W		LR30/15/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 15° Beam	
16W		LR30/15/30K/1200/xx	PAR30, 3000K, 1200 Lumen, E26, short neck, 15° Beam	
16W		LR30/25/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 25° Beam	
16W		LR30/25/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 25° Beam	
16W		LR30/25/30K/1200/WH	PAR30, 3000K, 1200 Lumen, E26, short neck, 25° Beam	
16W		LR30/40/27K/1100/xx	PAR30, 2700K, 1100 Lumen, E26, short neck, 40° Beam	
16W		LR30/40/30K/1125/xx	PAR30, 3000K, 1125 Lumen, E26, short neck, 40° Beam	
16W		LR30/40/30K/1200/xx	PAR30, 3000K, 1200 Lumen, E26, short neck, 40° Beam	
16W		LRP38/25/27K	PAR38, 2700K, 1025 Lumen, E26, 25° Beam	
16W		LRP38/25/30K	PAR38, 3000K, 1100 Lumen, E26, 25° Beam	
16W		LRP38/40/27K	PAR38, 2700K, 1025 Lumen, E26, 40° Beam	
16W		LRP38/40/30K	PAR38, 3000K, 1100 Lumen, E26, 40° Beam	
20W		LR38/25/30K/1450/SL	PAR38, 3000K, 1450 Lumen, E26, 15° Beam	
28W		LR38/15/27K/2000/xx	PAR38, 2700K, 2000 Lumen, E26	
28W		LR38/15/30K/2100/xx	PAR38, 3000K, 2100 Lumen, E26	
28W		LR38/25/27K/2000/xx	PAR38, 2700K, 2000 Lumen, E26	
28W		LR38/25/30K/2100/xx	PAR38, 3000K, 2100 Lumen, E26	
28W		LR38/40/27K/2000/xx	PAR38, 2700K, 2000 Lumen, E26	
28W		LR38/40/30K/2100/xx	PAR38, 3000K, 2100 Lumen, E26	
Switch		10W	A260FUS27B1	A19, 800 Lumen
	13W	75FU202	A19, 3000K, 1100 Lumen, E26	

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K



# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Maestro<sup>®</sup> C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Sylvania	6W	79643	A19, Soft White, 2700K, 450 Lumen, E26, clear
	6.5W	79162 (LED6.5A19/DIM/O/850/G5)	A19, 5000K, 450 Lumen, E26
	6.5W	79163 (LED6.5A19/DIM/O/850/G5)	A19, 2700K, 450 Lumen, E26
	7W	75169	G25, 475 Lumen, E26
	7W	75170	G25, 475 Lumen, E26
	7W	75180	G25, 475 Lumen, E26
	7W	79653 (LED7R20DIMSE830G3RP [LW])	R20, 3000K, 525 Lumen, E26,
	7W	79659 (LED7R20/DIM/SE/830/G3)	R20, 3000K, 525 Lumen, E26,
	7W	LED7A19/DIM/O/SE/830 (78214)	A19, 3000K to 2000K, 450 Lumen, E26, Sunset Effect
	7W	LED7A19/DIM/O/SE/830/RP (78213)	A19, 3000K to 2000K, 450 Lumen, E26, Sunset Effect
	8W	70419-6	4" Downlight, 600 Lumen, retrofit kit
	8W	70459-3	4" Downlight, 600 Lumen, retrofit kit
	8W	70643-3	4" Downlight, 600 Lumen, retrofit kit
	8W	73193-1	4" Downlight, 600 Lumen, retrofit kit
	8W	LED8A19DIMO827RP	A19, 2700K, 470 Lumen, E26
	8W	LED8PAR16/DIM/930/FL36/P/LW	PAR16, Soft White, 390 Lumen
	8W	LED8PAR16/GU10/DIM/930/FL36/RP	PAR16, GU10, Soft White, 390 Lumen
	8W	LED8R20/DIM/SE/830/RP	R20, Soft White, 2700K to 2000K, 520 Lumen
	10W	LED/600/RT4/830/FL80/RP	Recessed lighting kit, 3000K, 600 Lumen
	10W	LED/RT4/600/827/FL80	Recessed lighting kit, 2700K, 600 Lumen
	10W	LED10A19/DIM/O/SE/830	A19, 3000K, 800 Lumen
	10W	LED10A19/DIM/O/SE/830/RP (78215)	A19, 3000K, 800 Lumen
	10.5W	LED10A19/DIM/CL/O/827 (79146)	A19, 2700K, 800 Lumen, E26, 60WE
	10.5W	LED10A19/DIM/CL/O/827/BL (79147)	A19, 2700K, 800 Lumen, E26, 60WE
	10.5W	LED10A19/DIM/CL/O/827/G4 (79142)	A19, 2700K, 800 Lumen, E26, 60WE
	10.5W	LED10A19/DIM/CL/O/827/G4/BL (79143)	A19, 2700K, 800 Lumen, E26, 60WE
	10.5W	LED10A19/DIM/CL/O/827/RP (79644)	A19, 2700K, 800 Lumen, E26, 60WE
	10.5W	LED10A19/DIM/CL/O/850/G4 (79144)	A19, 5000K, 800 Lumen, E26, 60WE
	10.5W	LED10A19/DIM/CL/O/850/G4/BL (79145)	A19, 5000K, 800 Lumen, E26, 60WE
	11W	73195-0	Downlight
	11W	73497-0	Downlight
	11W	79654 (LED11BR30DIMSE830G3RP[LW])	BR30, 3000K, 800 Lumen, E26
	11W	79657 (LED11BR30/DIM/SE/830/G3)	BR30, 3000K, 800 Lumen, E26
	11W	79660 (LED11BR30DIMSE830G3RP)	BR30, 3000K, 800 Lumen, E26
	11W	LED11BR30/DIM/HO/827/G3 (78413)	BR30, 2700K, 800 Lumen, E26
	11W	LED11BR30/DIM/HO/827/G3/RP (78415)	BR30, 2700K, 800 Lumen, E26
	11W	LED11BR30/DIM/HO/827/G3/RP (79121)	BR30, 2700K, 800 Lumen, E26
	12W	72578 (LEDRT56700927FL80CEC)	5/6" Downlight, 2700K, 900 Lumen, GU24
	12W	72579-0	5/6" Downlight, 3000K, 900 Lumen, GU24
	12W	72593-0	5/6" Downlight, 4000K, 900 Lumen, GU24
	12W	LED12BR30/DIM/HO/827	BR30, 2700K, Medium base
	12W	LED12BR30/DIM/HO/827/HVP	BR30, 2700K, Medium base

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K



# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Maestro<sup>®</sup> C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Sylvania	12W	LED12BR30/DIM/SE/830/RP	BR30, Soft White, 2700K to 2000K, 850 Lumen
	14W	74031 (LED14PAR38DIM850FL40GL1WRP)	PAR38, 5000K, 1050 Lumen, E26
	14W	74032 (LED14PAR38DIM830NFL25GL1W)	PAR38, 3000K, 1050 Lumen, E26
	14W	74034 (LED14PAR38DIM830FL40GL1W)	PAR38, 3000K, 1050 Lumen, E26
	14W	74035 (LED14PAR38DIM830NFL25GL1W)	PAR38, 3000K, 1050 Lumen, E26
	14W	74036 (LED14PAR38DIM830WSP15GL1W)	PAR38, 3000K, 1050 Lumen, E26
	14W	74037(LED14PAR38DIM827FL40GL1W)	PAR38, 2700K, 1050 Lumen, E26
	14W	74065 (LED14PAR38DIM850FL40GL1WRP)	PAR38, 5000K, 1050 Lumen, E26
	14W	74066 (LED14PAR38DIM830FL40GL1WRP)	PAR38, 3000K, 1050 Lumen, E26
	14W	74067 (LED14PAR38DIM830FL40GL1WRP)	PAR38, 3000K, 1050 Lumen, E26
	15W	79655 (LED15BR40DIMSE830G3RP [LW])	BR40, 3000K, 1100 Lumen, E26
	15W	79661 (LED15BR40DIMSE830G3RP)	BR40, 3000K, 1100 Lumen, E26
	15W	LED15BR40/DIM/HO/827/G3/RP	BR40, Soft White, 2700K, 1100 Lumen, E26, Flood
	15W	LED15BR40/DIM/SE/830/G3	BR40, 3000K, 1100 Lumen, E26,
	16W	LED16BR40DIMHO827	BR40, 2700K, 1100Lumen
	17W	LED17PAR30LN/DIM/830/WSP15/P	PAR30, 3000K, 1200 Lumen, E26, spot
	17W	LED17PAR30LN/DIM/830/WSP20	PAR30, 3000K, 1200 Lumen, E26, wide spot
	18W	LED18PAR38/DIM/827/NFL25	PAR38, 2700K, 860 Lumen
	20W	LED20PAR38/DIM/930/FL40/P2	PAR38, 3000K, 1000 Lumen,
	20W	LED20PAR38DIM830FL40	PAR38, 3000K, 1300 Lumen
21W	LED21/PAR38/DIM/P/930/FL30/HVP	PAR38, Warm White, 3000K, 1100 Lumen, E26, 21W	
TCP	12W	LED12P30D27KNFL	PAR30,2700K,800 Lumen,E26
	17W	LED17BR40D27K (LED17BR40D)	BR40, 2700K, 1200 Lumen, E26
	17W	LED17HOP38D27KNFL (LED17P38D1)	PAR38, 2700K, 1550 Lumen, E26, Narrow Flood
	17W	LED17P38D24KNFL	PAR38, 2400K, 1105 Lumen, E26
Toshiba	13W	LDRB1327WE6USD2 (13BR40/27K-T)	BR40, 2700K, 950 Lumen
	13W	LDRB1340WE6USD2 (13BR40/40L-T)	BR40, 4000K, 1050 Lumen
Utilitech	3W	LG161/2DM/IF/LED	G16.5, Warm White, 3000K, 200 Lumen, E12 base, frosted
	4.5W	LR14DMLED	R14, Soft White, 2700K, 300 Lumen, E26, 40WE
	4.8W	LA15DM/CL/300/LED	A15, Warm White, 3000K, 300 Lumen, E26, clear
	4.8W	LA15DM/IF/300/LED	A15, Warm White, 3000K, 300 Lumen, E26, frosted
	4.8W	LA15DMC/CL/300/LED	A15, Warm White, 3000K, 300 Lumen, E12 base, clear
	4.8W	LCFFDM/300/LED	Candle, Warm White, 3000K, 300 Lumen, E12 base, frosted flame tip
4.8W	LEFCDM/300/LED	Candle, Warm White, 3000K, 300 Lumen, E26 base, clear flame tip	

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K



# Dimmable CFL & LED bulbs

Compatible with C•L® dimmers

List Updated March 18, 2016



## LED bulbs for Maestro® C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
	4.8W	LG161/2DM/CL/300/LED	G16.5, Warm White, 3000K, 300 Lumen, E12 base, clear
	4.8W	LG161/2DM/IF/300/LED	G16.5, Warm White, 3000K, 300 Lumen, E12 base, frosted
	4.8W	LGMDM/CL/300/LED	G16.5, Warm White, 3000K, 300 Lumen, E26, clear
	5.5W	LMR16GU10DMLEDG2	MR16, 2700K, 350 Lumen, GU10, Flood
	6.5W	LMR16/GU10/DM/LED	MR16, GU10 base
	6.5W	LMR16DMGU10	MR16, GU10 base
	6.5W	LR16DMLED	R16, Soft White, 2700K, 400 Lumen, E26, 40WE
	7.5W	LA19DM/GU24/LED	A19, 3000K, GU24
	7.5W	LA19DM/LED	A19, 3000K, 450 Lumen, E26
	7.5W	LA19DM/LEDG2	A19, 3000K, 450 Lumen
	7.5W	R20/DM/5K/LED	R20, 450 Lumen, E26
	8W	BPCER20/927/LED	R20, 450 Lumen, E26
	8W	LA19DM/5K/LED	A19, 5000K
	8W	LCFCDM500LED	Candle, 3000K, 500 Lumen, E12 candle base
	8W	LG25DM/LEDG2	G25, Warm White, 3000K, 510 Lumen, E26
	8W	LR20DM/LED†	R20, 2700K, 450 Lumen (90mA ridged reflector version)
	8W	R20/927/LED	R20, 450 Lumen, E26
	8W	R20/DM/LEDG2	R20, 450 Lumen, E26
	8W	R20DM/LEDG2/CAN	R20, 450 Lumen, E26
	8.5W	LMR16DMGU10/500/LED	MR16, Warm White, 3000K, 520 Lumen, GU10, 120V
	8.5W	LPAR20LEDG72	PAR20, 500 Lumen, 2PK
	9W	LR20HO/LED/G2	R20, Soft White, 650 Lumen, E26, flood
	9W	R20HO/LED/G2	R20, Soft White, 650 Lumen, E26, flood
	9.5W	AGOM800/5K/LED/CAN	A19, 810 Lumen, E26
	9.5W	AGOM800/927/LED	A19, 810 Lumen, E26
	9.5W	AGOM800/927/LED/CAN	A19, 810 Lumen, E26
	9.5W	AGOM800/LED/3/CAN	A19, 800 Lumen, E26
	9.5W	AGOM800/LED/CAN	A19, 800 Lumen, E26
	9.5W	BPAGOM800/5K/LED	A19, 810 Lumen, E26
	9.5W	BPAGOM800/LED	A19, 800 Lumen, E26
	9.5W	BPAGOM800/LED/TAR	A19, 800 Lumen, E26
	9.5W	BPAGOM800/LED/TV	A19, 800 Lumen, E26
	9.5W	BPCEAG800/927/LED/3	A19, 810 Lumen, E26
	9.5W	LPAR20/5K/LEDG5	PAR20, 5000K, 500 Lumen
	9.5W	LPAR20/LEDG5	PAR20, 3000K, 450 Lumen
	9.5W	LPAR20DM/SP/LED	PAR20, 3000K, 465 Lumen, Spot
	9.8W	LA19DM/800/LED/G2	A19, 3000K, 800 Lumen
	10W	LA19DM/800/5K/LEDG2	A19, 5000K
	10W	LA19DM/800/LEDG2	A19, 3000K, 800 Lumen
	11W	DLS02-04A27D1E-WH-F1	4" Downlight, 2700K, 600 Lumen, E26 retrofit
	11W	DLS02-04A27D1E-WH-F2	4" Downlight, 2700K, 600 Lumen, E26 retrofit 2pk
	11W	DLS02-41127D1E-WF1	4" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit
	12W	LPAR30L/LEDG7/2	PAR30L, 3000K, 800 Lumen, E26, long neck, 2PK
	13W	BPCEBR30/927/LED	BR30, 750 Lumen, E26
	13W	BR30/927/LED	BR30, 750 Lumen, E26
	13W	BR30/927/LED/CAN	BR30, 750 Lumen, E26
	13W	BR30/DM/LEDG2	BR30, 750 Lumen, E26
	13W	BR30DM/LED/CAN	BR30, 750 Lumen, E26
	13W	DLS03-06E30D1E-WH-F1	Downlight 3000K 700 Lumens 65WE
	13W	LBR30DM/LEDG2	BR30
	13.5W	LA19/OM800/LED	A19, 3000K, 800 Lumen, Omni Directional
	15W	15PAR30L/LEDG5	PAR30, 3000K, 790 Lumen, E26
	15W	BPCEPAR30/930/LED	PAR30, 3000K, 770 Lumen, E26
	15W	LBR30HO/LED/G2	BR30, Soft White, 1150 Lumen
	15W	LPAR30L/5K/LEDG5	PAR30, 5000K, 800 Lumen, long neck flood
	15W	LPAR30L/LEDG5	PAR30, 3000K, 790 Lumen, long neck flood
	15W	LPAR30LDM/SP/LED	PAR30, 3000K, 790 Lumen, long neck, spot

Utilitech

† Requires a minimum of 2 lamps  
 †† Requires a minimum of 3 lamps  
 © Lutron Electronics Co., Inc. | PN 368-3266K

# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## LED bulbs for Maestro<sup>®</sup> C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
Utilitech	15W	LPAR30S/LEDG5	PAR30, 3000K, 750 Lumen, short neck flood
	15W	PAR30/S/5K/LEDG5	PAR30, 3000K, 750 Lumen, E26
	15W	PAR30/S/LEDG5	PAR30, 3000K, 750 Lumen, E26
	15W	PAR30L/5K/LEDG5	PAR30, 3000K, 800 Lumen, E26
	15W	PAR30L/930/LED	PAR30, 3000K, 770 Lumen, E26
	15W	PAR30L/LEDG5	PAR30, 3000K, 800 Lumen, E26
	15.5W	BPCEAG1600/827/LED	A19, 1600 Lumen, E26
	16W	AGOM1600/5K/LED/CAN	A19, 1600 Lumen, E26
	16W	AGOM1600/LED/CAN	A19, 1600 Lumen, E26
	16W	BPAGOM1600/5K/LED	A19, 1600 Lumen, E26
	16W	BPAGOM1600/LED	A19, 1600 Lumen, E26
	16W	BPAGOM1600/LED/TAR	A19, 1600 Lumen, E26
	16W	LA19/OM1100R/LED	A19, 3000K, 1100 Lumen, Omni Directional
	16W	LBR40DM/LEDG2	BR40, 1065 Lumen, E26
	16W	LBR40DMLEDG2	BR40, 2700K, 1065 Lumen
	16W	LPAR38LEDG72	PAR38, 3000K, 950 Lumen, 2PK
	16W	LPAR38LEDG72	PAR38, 3000K, 950 Lumen, 2PK
	16.5W	PAR38/5K/LEDG5	PAR30, 3000K, 1000 Lumen, E26
	17W	BPCEBR40/DM/LED†	BR40
	17W	LBR40DM/LED†	BR40, 2700K, 1065 Lumen
	18W	BPCEPAR38/930/LED	PAR30, 3000K, 950 Lumen, E26
	18W	PAR38/930/LED	PAR30, 3000K, 950 Lumen, E26
	20W	20PAR38/LEDG5	PAR30, 3000K, 1035 Lumen, E26
	20W	DLS24-06C27D1E-WH-F1	5 or 6" Downlight 2700K 1200 Lumens 90WE
	20W	L20PAR38/LEDG5	PAR38, 3000K, 1000 Lumen, flood
	20W	LBR40HO/LED/G2	BR40, Soft White, 1400 Lumen
	20W	LPAR38/5K/LEDG5	PAR38, 5000K, 1000 Lumen, flood
	20W	LPAR38/LEDG5	PAR38, 3000K, 1000 Lumen, flood
	20W	LPAR38DM/SP/LED	PAR38, 3000K, 1000 Lumen, Spot
	20W	PAR38/LEDG5	PAR30, 3000K, 950 Lumen, E26
	20.5W	LPAR381400LEDG72	PAR38, 1450 Lumen, 2PK
	22W	LA/OM1600R/5K/LED	A21, Daylight, 5000K, 1600 Lumen
	22W	LA/OM1600R/LED	A21, Warm White, 3000K, 1600 Lumen
23W	LPAR38/1400/5K/LEDG5	PAR38, 5000K, 1400 Lumen	
23W	LPAR38/1400/LEDG5	PAR38, 3000K, 1400 Lumen	
Westinghouse	6W	33098	A19, 3000K, 470 Lumen
	6.5W	03425	A19, 2700K, 450 Lumen, E26, 40WE
	7W	33012	Par20, 3000K, 415 Lumen
	8W	03011	G25, 3000K, 430 Lumen
	8.5W	43000	R30, 2700K, 650 Lumen, flood
	9W	03563	BR30, 2700K, 750 Lumen, E26
	10W	03439	A19, 3000K, 800 Lumen, E26, 60WE
	10W	03696	A19, 2700K, 790 Lumen, E26, 60WE
	17W	33014	PAR38, 3000K, 1200 Lumen, flood
	17W	33064	PAR38, 3000K, 1200 Lumen, flood

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K

# Dimmable CFL & LED bulbs

Compatible with C•L<sup>®</sup> dimmers

List Updated March 18, 2016



## CFL bulbs for Maestro<sup>®</sup> C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



Brand	Wattage	Model	Description
EcoSmart	5W	8TC05 <sup>†</sup>	Candle, (ES5CCDF052, ES9CCDF052)
	5W	8TC05F <sup>†</sup>	Candle, Torpedo Tip, 2700K, 200 Lumen
	5W	8TFC05F <sup>†</sup>	Candle, Flame Tip, 2700K, 200 Lumen
	11W	BPESL11R20/DM/ESM	R20, Soft White
	14W	40114	Spiral, Soft White (ES5M814DIM2, ES9M814DIM2)
	14W	2R2014DIM	R20, 2700K, 410 Lumen
	15W	2R3015DIM	R30 Flood, Soft White (ES5R315DIM2)
	15W	2R3015DIM35K	R30 Flood, Bright White (ES5R315DIM35K)
	15W	2R3015DIM50K	R30 Flood, Daylight (ES5R315DIM250K)
Feit	23W	40123	Spiral, Soft White (ES5M823DIM2)
	11W	BPESL11R20/DM	R20
	15W	BPESL15T/DM	Spiral
	23W	BPESL23R40/DIM	R40
GE	23W	BPESL23T/DM	Spiral
	26W	FLE26/2/DVR/40	R40
Philips	26W	FLE26HT3/2/DV/SW	Spiral
	20W	EL/A R40 Dim 20W	R40
Sylvania	5W	CF5EL/B10/827/L/DIM <sup>†</sup>	Candle
	5W	CF5EL/B10C/DIM/827/ADP <sup>†</sup>	Candle
	5W	CF5EL/DEC/DIM <sup>†</sup>	Candle
	14W	CF14EL/TWIST/DIM	Spiral
	24W	CF24EL/TWIST/DIM	Spiral
TCP	5W	8TC05F <sup>†</sup>	Candle
	5W	8TFC05F <sup>†</sup>	Candle, flame tip
	14W	40114	Spiral
	14W	2R2014DIM	R20, 2700K, 410 Lumen
	14W	4R2014TD	R20, TruDim, 2700K
	14W	4R2014TD30K	R20, TruDim, 3000K
	14W	4R2014TD35K	R20, TruDim, 3500K
	14W	4R2014TD41K	R20, TruDim, 4100K
	14W	4R2014TD50K	R20, TruDim, 5000K
	14W	4R2014TD65K	R20, TruDim, 6500K
	15W	2R3015DIM	R30, Soft White, 2700K
	16W	4R3016TD	R30, TruDim, 2700K
	16W	4R3016TD30K	R30, TruDim, 3000K
	16W	4R3016TD35K	R30, TruDim, 3500K
	16W	4R3016TD41K	R30, TruDim, 4100K
	16W	4R3016TD50K	R30, TruDim, 5000K
	16W	4R3016TD65K	R30, TruDim, 6500K
	23W	40123	Spiral
	Utilitech	11W	LBP11R20DM
15W		LBP15TDM	Spiral
23W		LBP23R40DM	R40
23W		LBP23TDM	Spiral

<sup>†</sup> Requires a minimum of 2 lamps

<sup>††</sup> Requires a minimum of 3 lamps

© Lutron Electronics Co., Inc. | PN 368-3266K