

2X4' 40W TROFFER TITANIUM LED SERIES

Preliminary Specifications



PRO



- ⌚ Exceptional efficacy meets DLC Premium requirements
- ⌚ High performance lighting distribution and low glare lens
- ⌚ 120-277V circuit and 0-10V dimming control compatible
- ⌚ Modern look and high quality architectural finish
- ⌚ Easy installation for new construction or retrofit



EFFICIENCY AT WORK



2X4' 40W TROFFER TITANIUM LED SERIES

Preliminary Specifications



SPECIFICATIONS*

| Product Model | 97791 40TROF24DIM/830/277V (MTO) | 97792 40TROF24DIM/835/277V | 97793 40TROF24DIM/840/277V | 97794 40TROF24DIM/850/277V (MTO) |
|------------------------------------|--|-------------------------------|-------------------------------|--|
| Type | 2x4' Troffer | 2x4' Troffer | 2x4' Troffer | 2x4' Troffer |
| Power (W) | 40 | 40 | 40 | 40 |
| Voltage - Frequency | 120-277V 50-60Hz | 120-277V 50-60Hz | 120-277V 50-60Hz | 120-277V 50-60Hz |
| Color Temp. (ANSI) | Warm White 3000K | Neutral White 3500K | Cool White 4000K | Daylight 5000K |
| CRI (Ra) | 80 | 80 | 80 | 80 |
| Typical lumens (lm) | 4120 | 4280 | 4400 | 4520 |
| Efficacy (LPW) | 103 | 107 | 110 | 113 |
| Beam Angle | 120° | 120° | 120° | 120° |
| Dimmable | Yes | Yes | Yes | Yes |
| Power Factor | 0.9 | 0.9 | 0.9 | 0.9 |
| THD | <20% | <20% | <20% | <20% |
| Rated Lifetime - L70 (hrs.) | 50,000 | 50,000 | 50,000 | 50,000 |
| Dia. x MOL | 23.94"x47.72" (608x1212mm) | 23.94"x47.72" (608x1212mm) | 23.94"x47.72" (608x1212mm) | 23.94"x47.72" (608x1212mm) |
| Weight (lb. / g) | 15.34lb / 6.96kg | 15.34lb / 6.96kg | 15.34lb / 6.96kg | 15.34lb / 6.96kg |

* Specification data is preliminary and subject to change

** Not intended for use in totally enclosed fixtures

*** Suitable for damp locations. Not for use where directly exposed to the weather or water

Ref.# DS109-TROF-40W-2X4