



D-Series LED Flood Luminaire, Size 2

Compact Size. Incredible Output. Small and compact, the D-Series Size 2 can be effortlessly concealed throughout a site – producing a dramatic impact with a minimal presence. With its advanced LED technology, the Size 2 delivers high lumen packages without the cumbersome dayform and energy demands of traditional sources.

Quick **FACTS**

- 175-250W MH replacement
- Lumen packages up to 7,800 lumens
- Efficacies of up to 113 lumens per watt
- Multiple optics, covering spot to wide flood distribution
- Available in 3000K, 4000K & 5000K CCT
- 6kV surge protection
- Weight: 10.2 lbs; EPA: 0.80 ft²

Key **FEATURES**

- Energy savings of up to 80% vs.comparable metal halide luminaires. Saves up to \$106 per luminaire, per year over 250W metal halide
- 43-49% more lumens per watt than comparable LED luminaires
- 20+ years expected service life with high lumen maintenance - L80/100,000 hours
- Adjustable knuckle mount allows for precise aiming
- Control options include photocell and dimming



d³series
better lighting from every angle™



D-Series LED Flood Luminaire, Size 2

ORDERING INFORMATION

EXAMPLE: DSXF2 LED 4 A530/40K MSP MVOLT THK DDBXD

| DSXF2 LED | Light Engines | Performance Package | Distribution | Voltage | Mounting | Options | Finish (required) |
|-----------|--|--|---|--|---|--|---|
| DSXF2 LED | 3 Three COB engines ¹ 4 Four COB engines | 530 mA options: A530/30K 3000K A530/40K 4000K A530/50K 5000K | NSP Narrow spot MSP Medium spot MFL Medium flood FL Flood WFL Wide flood WFR Wide flood, rectangular HMF Horizontal flood | MVOLT ² 120 ² 208 ² 240 ² 277 ² 347 480 | Shipped included THK Knuckle with 1/2" NPS threaded pipe YKC62 Yoke with 16-3 SO cord Shipped separately³ DSXF1/2TS Tenon slipfitter (2-3/8" O.D. THK required) FTS CG6 Tenon slipfitter (2-7/8" O.D. YKC62 required) | Shipped installed PE Photocontrol, button style ⁴ DMG 0-10V dimming driver (no controls) ^{1,5} SF Single fuse (120, 277, 347V) ⁶ DF Double fuse (208, 240, 480V) ⁶ Shipped separately³ UBV Upper/bottom visor (universal) FV Full visor VG Vandal guard | DDBXD Dark bronze DBLXD Black DNAXD Natural aluminum DWHXD White |

Stock configurations are offered for shorter lead times:

| Standard Part Number | Stock Part Number |
|--|------------------------|
| DSXF2 LED 3 A530/40K WFL MVOLT THK DDBXD | DSXF2 LED 3 40K |
| DSXF2 LED 3 A530/50K WFL MVOLT THK DDBXD | DSXF2 LED 3 50K |
| DSXF2 LED 4 A530/40K WFL MVOLT THK DDBXD | DSXF2 LED 4 40K |
| DSXF2 LED 4 A530/50K WFL MVOLT THK DDBXD | DSXF2 LED 4 50K |

Accessories

Ordered and shipped separately.

| | |
|-------------------|--|
| DSXF1/2TS DDBXD U | Slipfitter for 1-1/4" to 2-3/8" OD tenons; mates with 1/2" threaded knuckle (specify finish) |
| FTS CG6 DDBXD U | Slipfitter for 2-3/8" to 2-7/8" OD tenons; mates with yoke mount (specify finish) |
| FRWB DDBXD U | Radius wall bracket, 2-3/8" OD tenon (specify finish) |
| FSPB DDBXD U | Steel square pole bracket, 2-3/8" OD tenon (specify finish) |
| DSXF2UBV DDBXD U | Upper/bottom visor accessory (specify finish) |
| DSXF2FV DDBXD U | Full visor accessory (specify finish) |
| DSXF2VG U | Vandal guard accessory |

For more mounting options, visit our [Floodlighting Accessories](#) pages.

NOTES

- Not available with 347 or 480V.
- MVOLT driver operates on any line voltage from 120-277V. Specify 120, 208, 240 or 277 options only when ordering with fusing (SF, DF options) or photocontrol (PE).
- Also available as separate accessories; see Accessories information at left.
- Photocontrol (PE) requires 120, 208, 240, 277 or 347 voltage option.
- Not available with three-engine product (DSXF2 LED 3).
- Single fuse (SF) requires 120, 277 or 347 voltage option. Double fuse (DF) requires 208, 240 or 480 voltage option.

