



# D-Series Size 1 LED Wall Luminaire



d#series

## Specifications Luminaire

**Width:** 13-3/4" (34.9 cm) **Weight:** 12 lbs (5.4 kg)

**Depth:** 10" (25.4 cm)


**Height:** 6-3/8" (16.2 cm)

## Back Box (BBW, ELCW)

**Width:** 13-3/4" (34.9 cm) **BBW Weight:** 5 lbs (2.3 kg)

**Depth:** 4" (10.2 cm) **ELCW Weight:** 10 lbs (4.5 kg)

**Height:** 6-3/8" (16.2 cm)



## Introduction

The D-Series Wall luminaire is a stylish, fully integrated LED solution for building-mount applications. It features a sleek, modern design and is carefully engineered to provide long-lasting, energy-efficient lighting with a variety of optical and control options for customized performance.

With an expected service life of over 20 years of nighttime use and up to 74% in energy savings over comparable 250W metal halide luminaires, the D-Series Wall is a reliable, low-maintenance lighting solution that produces sites that are exceptionally illuminated.

## Ordering Information

**EXAMPLE:** DSXW1 LED 20C 1000 40K T3M MVOLT DDBTXD

Series	LEDs	Drive Current	Color temperature	Distribution	Voltage	Mounting	Control Options	Other Options	Finish (required)
DSXW1 LED	10C 10 LEDs (one engine)	350 350 mA	30K 3000 K	T2S Type II Short	MVOLT <sup>1</sup>	Shipped included (blank) Surface mounting bracket	Shipped installed PE Photoelectric cell, button type <sup>4</sup>	Shipped installed SF Single fuse (120, 277 or 347V) <sup>7</sup>	DDBXD Dark bronze
		530 530 mA	40K 4000 K	T2M Type II Medium	120 <sup>1</sup>				
DSXW1 LED	20C 20 LEDs (two engines)	700 700 mA	50K 5000 K	T3S Type III Short	208 <sup>1</sup>	BBW Surface-mounted back box (for conduit entry) <sup>3</sup>	DMG 0-10V dimming driver (no controls)	DF Double fuse (208, 240 or 480V) <sup>7</sup>	DNAXD Natural aluminum
		1000 1000 mA (1 A)	AMBPC Amber phosphor converted	T3M Type III Medium	240 <sup>1</sup>				
				T4M Type IV Medium	277 <sup>1</sup>				
				TFTM Forward Throw Medium	347 <sup>2</sup>				
				ASVDF Asymmetric diffuse	480 <sup>2</sup>				
						PIRH 180° motion/ambient light sensor, 15-30' mtg ht <sup>5</sup>	SPD Separate surge protection <sup>9</sup>	DSSXD Sandstone	
						ELCW Emergency battery backup (includes external component enclosure) <sup>6</sup>		DDBTXD Textured dark bronze	
								Shipped separately	
								BSW Bird-deterrent spikes	DBLBXD Textured black
								WG Wire guard	DNATXD Textured natural aluminum
								VG Vandal guard	DWHGXD Textured white
								DDL Diffused drop lens	DSSTXD Textured sandstone

### NOTES

- MVOLT driver operates on any line voltage from 120-277V (50/60 Hz). Specify 120, 208, 240 or 277 options only when ordering with fusing (SF, DF options), or photocontrol (PE option).
- Only available with 20C, 700mA or 1000mA. Not available with PIR or PIRH.
- Back box ships installed on fixture. Cannot be field installed. Cannot be ordered as an accessory.
- Photocontrol (PE) requires 120, 208, 240, 277 or 347 voltage option. Not available with motion/ambient light sensors (PIR or PIRH).
- PIR specifies the Sensor Switch SBGR-10-ODP control; PIRH specifies the Sensor Switch SBGR-6-ODP control; see Motion Sensor Guide for details. Includes ambient light sensor. Not available with "PE" option (button type photocell). Dimming driver standard. Not available with 20 LED/1000 mA configuration (DSXW1 LED 20C 1000).
- Cold weather (-20C) rated. Not compatible with conduit entry applications. Not available with BBW mounting option. Not available with fusing. Not available with 347 or 480 voltage options. Emergency components located in back box housing. Emergency mode IES files located on product page at [www.lithonia.com](http://www.lithonia.com)
- Single fuse (SF) requires 120, 277 or 347 voltage option. Double fuse (DF) requires 208, 240 or 480 voltage option. Not available with ELCW.
- Also available as a separate accessory; see Accessories information.
- See the electrical section on page 3 for more details.

## Accessories

Ordered and shipped separately.

DSXWHS U	House-side shield (one per light engine)
DSXWBSW U	Bird-deterrent spikes
DSXW1WG U	Wire guard accessory
DSXW1VG U	Vandal guard accessory

## Performance Data

### Lumen Output

Lumen values are from photometric tests performed in accordance with IESNA LM-79-08. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. Contact factory for performance data on any configurations not shown here.

LEDs	Drive Current (mA)	System Watts	Dist. Type	30K					40K					50K					AMBER						
				Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW		
10C (10 LEDs)	530mA	20 W	T2S	1,843	1	0	1	92	1,956	1	0	1	98	1,729	1	0	1	86	1,264	0	0	1	63		
			T2M	1,756	1	0	1	88	1,864	1	0	1	93	1,648	1	0	1	82	1,205	0	0	1	60		
			T3S	1,822	0	0	1	91	1,934	0	0	1	97	1,710	0	0	1	86	1,250	0	0	1	63		
			T3M	1,804	1	0	1	90	1,914	1	0	1	96	1,693	1	0	1	85	1,237	0	0	1	62		
			T4M	1,767	1	0	1	88	1,876	1	0	1	94	1,658	0	0	1	83	1,212	0	0	1	61		
			TFTM	1,837	0	0	1	92	1,950	0	0	1	98	1,724	0	0	1	86	1,260	0	0	1	63		
			ASYDF	1,642	1	0	1	82	1,743	1	0	1	87	1,541	1	0	1	77	1,127	0	0	1	56		
			ASDF	2,272	1	0	1	84	2,409	1	0	1	89	2,421	1	0	1	90	1,544	0	0	1	57		
	700mA	27 W	T2M	2,165	1	0	1	80	2,296	1	0	1	85	2,307	1	0	1	85	1,472	0	0	1	55		
			T3S	2,247	1	0	1	83	2,382	1	0	1	88	2,394	1	0	1	89	1,527	0	0	1	57		
			T3M	2,224	1	0	1	82	2,358	1	0	1	87	2,370	1	0	1	88	1,512	0	0	1	56		
			T4M	2,179	1	0	1	81	2,310	1	0	1	86	2,322	1	0	1	86	1,481	0	0	1	55		
			TFTM	2,265	1	0	1	84	2,401	1	0	1	89	2,413	1	0	1	89	1,539	0	0	1	57		
			ASYDF	2,025	1	0	1	75	2,147	1	0	1	80	2,158	1	0	1	80	1,376	1	0	1	51		
			T2S	3,011	1	0	1	75	3,190	1	0	1	80	3,202	1	0	1	80	2,235	1	0	1	58		
			T2M	2,870	1	0	1	72	3,040	1	0	1	76	3,051	1	0	1	76	2,130	1	0	2	55		
	1000mA	40 W	T3S	2,978	1	0	1	74	3,155	1	0	1	79	3,166	1	0	1	79	2,210	1	0	2	57		
			T3M	2,948	1	0	1	74	3,123	1	0	1	78	3,134	1	0	1	78	2,187	1	0	2	56		
			T4M	2,888	1	0	1	72	3,059	1	0	1	76	3,071	1	0	1	77	2,143	1	0	2	55		
			TFTM	3,002	1	0	1	75	3,180	1	0	1	80	3,192	1	0	1	80	2,228	1	0	2	57		
			ASYDF	2,684	1	0	1	67	2,843	1	0	1	71	2,854	1	0	1	71	1,991	1	0	2	51		
			T2S	3,649	1	0	1	101	3,876	1	0	1	108	3,429	1	0	1	95	2,504	1	0	1	70		
			T2M	3,478	1	0	1	97	3,694	1	0	1	103	3,267	1	0	1	91	2,387	1	0	1	66		
			T3S	3,609	1	0	1	100	3,833	1	0	1	106	3,390	1	0	1	94	2,477	1	0	1	69		
20C (20 LEDs)	530mA	36 W	T3M	3,572	1	0	1	99	3,794	1	0	1	105	3,356	1	0	1	93	2,451	1	0	2	68		
			T4M	3,500	1	0	2	97	3,717	1	0	2	103	3,288	1	0	1	91	2,402	1	0	1	67		
			TFTM	3,638	1	0	1	101	3,864	1	0	1	107	3,418	1	0	1	95	2,496	1	0	1	69		
			ASYDF	3,252	1	0	2	90	3,454	1	0	2	96	3,056	1	0	2	85	2,232	1	0	1	62		
			700mA	47 W	T2S	4,502	1	0	1	96	4,776	1	0	1	102	4,794	1	0	1	102	3,065	1	0	1	65
					T2M	4,290	1	0	1	91	4,552	1	0	1	97	4,569	1	0	1	97	2,921	1	0	1	62
					T3S	4,452	1	0	1	95	4,723	1	0	2	100	4,741	1	0	2	101	3,031	1	0	1	64
					T3M	4,407	1	0	2	94	4,675	1	0	2	99	4,693	1	0	2	100	3,000	1	0	1	64
	T4M	4,318			1	0	2	92	4,581	1	0	2	97	4,598	1	0	2	98	2,939	1	0	1	63		
	TFTM	4,488			1	0	2	95	4,761	1	0	2	101	4,779	1	0	2	102	3,055	1	0	1	65		
	ASYDF	4,012			1	0	2	85	4,257	1	0	2	91	4,273	1	0	2	91	2,732	1	0	1	58		
	ASDF	5,963			1	0	1	80	6,327	1	0	1	84	6,351	1	0	1	85	4,429	1	0	1	61		
	1000mA	74 W	T2M	5,683	1	0	2	76	6,029	1	0	2	80	6,052	1	0	2	81	4,221	1	0	2	58		
			T3S	5,896	1	0	2	79	6,256	1	0	2	83	6,280	1	0	2	84	4,380	1	0	2	60		
			T3M	5,837	1	0	2	78	6,193	1	0	2	83	6,216	1	0	2	83	4,335	1	0	2	59		
			T4M	5,719	1	0	2	76	6,067	1	0	2	81	6,090	1	0	2	81	4,248	1	0	2	58		
			TFTM	5,944	1	0	2	79	6,307	1	0	2	84	6,330	1	0	2	84	4,415	1	0	2	60		
			ASYDF	5,314	1	0	2	71	5,638	2	0	2	75	5,660	2	0	2	75	3,947	1	0	2	54		

## Performance Data

### Lumen Ambient Temperature (LAT) Multipliers

Use these factors to determine relative lumen output for average ambient temperatures from 0-40°C (32-104°F).

Ambient		Lumen Multiplier
0°C	32°F	1.02
10°C	50°F	1.01
20°C	68°F	1.00
<b>25°C</b>	<b>77°F</b>	<b>1.00</b>
30°C	86°F	1.00
40°C	104°F	0.98

### Projected LED Lumen Maintenance

Data references the extrapolated performance projections for the **DSXW1 LED 20C 1000** platform in a **25°C ambient**, based on 10,000 hours of LED testing (tested per IESNA LM-80-08 and projected per IESNA TM-21-11).

To calculate LLF, use the lumen maintenance factor that corresponds to the desired number of operating hours below. For other lumen maintenance values, contact factory.

Operating Hours	0	25,000	50,000	100,000
Lumen Maintenance Factor	1.0	0.95	0.93	0.88


### Electrical Load

LEDs	Drive Current (mA)	System Watts	Current (A)					
			120V	208V	240V	277V	347V	480V
10C	350	14 W	0.13	0.07	0.06	0.06	-	-
	530	20 W	0.19	0.11	0.09	0.08	-	-
	700	27 W	0.25	0.14	0.13	0.11	-	-
	1000	40 W	0.37	0.21	0.19	0.16	-	-
20C	350	25 W	0.23	0.13	0.12	0.10	-	-
	530	36 W	0.33	0.19	0.17	0.14	-	-
	700	47 W	0.44	0.25	0.22	0.19	0.15	0.11
	1000	75 W	0.69	0.40	0.35	0.30	0.23	0.17

## Photometric Diagrams

To see complete photometric reports or download .ies files for this product, visit Lithonia Lighting's D-Series Wall Size 1 homepage.

Isofootcandle plots for the DSXW1 LED 20C 1000 40K. Distances are in units of mounting height (15').



## Options and Accessories



T3M (left), ASYDF (right) lenses



HS - House-side shields



BSW - Bird-deterrent spikes



WG - Wire guard



VG - Vandal guard



DDL - Diffused drop lens

## FEATURES & SPECIFICATIONS

### INTENDED USE

The energy savings, long life and easy-to-install design of the D-Series Wall Size 1 make it the smart choice for building-mounted doorway and pathway illumination for nearly any facility.

### CONSTRUCTION

Two-piece die-cast aluminum housing has integral heat sink fins to optimize thermal management through conductive and convective cooling. Modular design allows for ease of maintenance. The LED driver is mounted to the door to thermally isolate it from the light engines for low operating temperature and long life. Housing is completely sealed against moisture and environmental contaminants (IP65).

### FINISH

Exterior parts are protected by a zinc-infused Super Durable TGIC thermoset powder coat finish that provides superior resistance to corrosion and weathering. A tightly controlled multi-stage process ensures a minimum 3 mils thickness for a finish that can withstand extreme climate changes without cracking or peeling. Available in textured and non-textured finishes.

### OPTICS

Precision-molded proprietary acrylic lenses provide multiple photometric distributions tailored specifically to building mounted applications. Light engines are available in 3000 K (80 min. CRI), 4000 K (70 min. CRI) or 5000 K (70 CRI) configurations.

### ELECTRICAL

Light engine(s) consist of 10 high-efficacy LEDs mounted to a metal-core circuit board to maximize heat dissipation and promote long life (L88/100,000 hrs at 25°C). Class 1 electronic drivers have a

power factor >90%, THD <20%, and a minimum 2.5KV surge rating. When ordering the SPD option, a separate surge protection device is installed within the luminaire which meets a minimum Category C Low (per ANSI/IEEE C62.41.2).

### INSTALLATION

Included universal mounting bracket attaches securely to any 4" round or square outlet box for quick and easy installation. Luminaire has a slotted gasket wireway and attaches to the mounting bracket via corrosion-resistant screws.

### LISTINGS

CSA certified to U.S. and Canadian standards. Rated for -40°C minimum ambient.

DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at [www.designlights.org](http://www.designlights.org) to confirm which versions are qualified.

### WARRANTY

Five year limited warranty. Full warranty terms located at [www.acuitybrands.com/CustomerResources/Terms\\_and\\_conditions.aspx](http://www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx).

**Note:** Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25°C. Specifications subject to change without notice.