

The Low-Bay/High-Bay Luminaire With the Highest Lumens Per Dollar Available Today.

EXCEPTIONAL

Performance

Cree does it again with the CXB Series, which can replace up to 250W and 400W HID low-bay and high-bay fixtures at the highest lumens per dollar among competing LED luminaires available today. And it's priced to enable payback at less than 3 years.

VERSATILE

Design & Aesthetics

With a compact, lightweight construction, you have your choice of aluminum, clear and white acrylic reflectors with optional bottom lenses — making the CXB Series ideal for education, grocery, gymnasium and industrial applications.

FLEXIBLE

Mounting Options

Weighing 50% less than traditional metal halide high- and low-bay luminaires and available in traditional mounting options, the CXB Series offers a quick and easy installation for seamless upgrade and new construction opportunities.

LONG-TERM

Value

Reap the benefits of long-term financial savings with lower energy bills and reduced maintenance costs — all by replacing those difficult-to-reach, elevated mounted fluorescent and HID fixtures with the CXB Series.







White Acrylic Reflector



Anodized Matte Aluminum Reflector



CXB Series LED Low-Bay/High-Bay Luminaire

At Cree, we're redefining low/high-bay LED performance. With multiple lumen packages, reflectors and lenses, designing the ideal solution for your application is quick and easy. Exceptional rated lifetimes, zero restrike time and compact lightweight construction allow you to put the CXB Series in the ceiling and forget about it – making it ideal for grocery, gymnasium, industrial, retail, manufacturing and warehouse applications.

Performance Summary Delivered Light Output: 18,000 or 24,000 median lumens Input Power: 160 or 240 watts CRI: 80 CCT: 4000K, 5000K Input Voltage: 120-277 VAC or 347-480 VAC Warranty: 10 years Mounting: J-box, pendant, and hook, cord & plug Weight: Maximum 14 lbs.

Die-cast aluminum heatsink. Low-profile, lightweight design provides ease of installation. Mounting choices of direct J-box/pendant and hook, cord & plug.

Dimming: 0-10V standard

Construction & Materials

JP Mount has provision to accept 3/4" IP pendant (by others).

HC Mount is provided with spring lock hook for mounting and factory-installed 6' power

JP Mount mounts directly over existing 4" single gang square, rectangular and octagonal

Factory calibrated to hang straight.

cord and plug.

junction boxes for direct mount.



Lens Options











