

The Superior Life[®] LED Panel Light with super bright SMD LEDs offers high luminous efficiency. They consume up to 80% less energy, significantly reducing operating costs and are environmentally friendly. The slim attractive design of our LED Panel Lights are perfect for offices, hotels, restaurants, schools, factories, galleries, retail, hospitals, airports and other architectural features.

BRIGHT AND CONSISTENT

The unique construction of Superior Life[®] LED Panels offers uniform light distribution throughout the face creating an even glare-free illumination that ensures clean bright whites and vibrant colors.

- NO DELAY, QUICK START UP
 No Flickering or Humming
- REDUCED HEAT OUTPUT
 Our Superior Life[®] LED Panels remain cool to the touch, increasing placement possibilities and eliminating the need for ventilation.
- ZERO MAINTENANCE
- VIBRATION AND WATER RESISTANT
- ECO-FRIENDLY, MERCURY FREE
- COMPACT LIGHTWEIGHT DESIGN

SIMPLE INSTALLATION

Hanging or mounting kits sold separately. Earthquake proof hooks included with V5 panels.

Note: DLC items are certified at the time of production. Please visit www.designlights.org for the most recent list of qualified products. • Published lumens on LED products are approximate and may vary slightly.



(
	0.4"

ITEM#	DESCRIPTION	WATT	ССТ	LM	LM/W	CRI	VOLTS	LIFE	FLUOR. EQUIV.	CASE
PREMIUM PANELS										
55301	LED 2X2 PANEL 20W/40K/120-277V/DIMMABLE/V5 - SL® DLC	20	40K	2632	128	83	120-277V	50K	50W	2
55302	LED 2X2 PANEL 20W/50K/120-277V/DIMMABLE/V5 - SL [®] DLC	20	50K	2650	130	82	120-277V	50K	50W	2
55304	LED 2X2 PANEL 32W/40K/120-277V/DIMMABLE/V5 - SL® DLC	32	40K	4081	127	83	120-277V	50K	100W	2
55305	LED 2X2 PANEL 32W/50K/120-277V/DIMMABLE/V5 - SL® DLC	32	50K	4111	129	82	120-277V	50K	100W	2
55310	LED 2X4 PANEL 36W/40K/120-277V/DIMMABLE/V5 - SL [®] DLC	36	40K	4637	126	82	120-277V	50K	150W	2
55311	LED 2X4 PANEL 36W/50K/120-277V/DIMMABLE/V5 - SL [®] DLC	36	50K	5000	128	83	120-277V	50K	150W	2
55314	LED 2X4 PANEL 50W/50K/120-277V/DIMMABLE/V5 - SL [®] DLC	50	50K	6353	127	82	120-277V	50K	200W	2
55313	LED 2X4 PANEL 50W/40K/120-277V/DIMMABLE/V5 - SL® DLC	50	40K	6243	129	83	120-277V	50K	200W	2
	ARD PANELS									
55170	LED 1X4 PANEL 35W/40K/120-277V/DIMMABLE/V4 - SL®	35	40K	3500	90	83	120-277V	50K	75W	2
55283	LED 1X4 PANEL 37W/40K/120-277V/DIMMABLE/V5 - SL® DLC	37	40K	4673	127	83	120-277V	50K	75W	2
55284	LED 2X2 PANEL 40W/30K/120-277V/DIMMABLE/V5 - SL® DLC	40	30K	4027	101	83	120-277V	50K	100W	2
55176	LED 2X2 PANEL 40W/50K/120-277V/DIMMABLE/V4 - SL®	40	50K	4000	95	83	120-277V	50K	100W	2
55285	LED 2X2 PANEL 40W/40K/120-277V/DIMMABLE/V5 - SL® DLC	40	40K	4174	104	83	120-277V	50K	100W	2
55286	LED 2X2 PANEL 40W/50K/120-277V/DIMMABLE/V5 - SL [®] DLC	40	50K	4322	106	83	120-277V	50K	100W	2
55287	LED 2X4 PANEL 50W/30K/120-277V/DIMMABLE/V5 - SL [®] DLC	50	30K	5255	104	83	120-277V	50K	150W	2
55288	LED 2X4 PANEL 50W/40K/120-277V/DIMMABLE/V5 - SL [®] DLC	50	40K	5311	105	83	120-277V	50K	150W	2
55289	LED 2X4 PANEL 50W/50K/120-277V/DIMMABLE/V5 - SL [®] DLC	50	50K	5368	107	83	120-277V	50K	150W	2
55290	LED 2X4 PANEL 75W/30K/120-277V/DIMMABLE/V5 - SL [®] DLC	75	30K	7426	99	83	120-277V	50K	200W	2
55291	LED 2X4 PANEL 75W/40K/120-277V/DIMMABLE/V5 - SL® DLC	75	40K	7659	101	83	120-277V	50K	200W	2
55292	LED 2X4 PANEL 75W/50K/ 120-277V/DIMMABLE/V5 - SL® DLC	75	50K	7882	103t	83	120-277V	50K	200W	2
55182	LED 2X4 PANEL 75W/40K/120-277V/DIMMABLE/V4 - SL®	75	40K	7500	95	83	120-277V	50K	200W	2
ACCESS										
55293*	1x4 SURFACE MOUNTED KIT FOR LED V5 PANEL/WHITE - SL®									10
55294*	2x2 SURFACE MOUNTED KIT FOR LED V5 PANEL/WHITE - SL®									10
55295*	2x4 SURFACE MOUNTED KIT FOR LED V5 PANEL/WHITE - SL®									10
20127	2x2 SUSPENDED CABLE MOUNTING KIT FOR LED PANEL - SL® (39.4" L x									1
55297	1x4 or 2x4 SUSPENDED CABLE MOUNTING KIT FOR LED PANEL - SL® (39.4	4″ L x 0.06″ D	01A; 44 LE	8 Pull Test)					1
55280	EMERGENCY PACK FOR LED FIXTURE 15W/90 MIN/V5 - SL®									10
55281	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN/V5 - SL®									10

*Surface Mount Kits are not compatible with the V4 LED Panels (551XX)