LED T8 | DIRECT REPLACEMENT



PRODUCT FEATURES

- Easy Plug-and-Play Installation No Rewiring Required
- Operates with Electronic Ballasts¹
- Identical Look to Standard Fluorescent Lamp
- Full Glass Lens with 240 Degree Light Distribution
- High Efficacy with 50% Energy Savings
- UL Listed for Direct Fuorescent Lamp Replacement
- _
- ETL Sanitation Listed for Food Service Applications
- 5-Year Warranty



APPLICATIONS

- Office Buildings/Schools
- Warehouse
- Manufacturing Facilities
- Parking Garages

| Model Number | ² Lamp Type | Base | Watts / Replaced | Lumens | CCT | MOL | Distribution | Certification | Warranty |
|----------------|------------------------|------|------------------|---------|-------------------------|-----|--------------|---------------|----------|
| LBT8F12xxB | Plug-n-Play | G13 | 9W / 17W | 1200 lm | 3500K 4100K 5000K | 24" | 240° | UL | 5-Years |
| LBT8F16xxB-3FT | Plug-n-Play | G13 | 13W / 32W | 1650 lm | 3500K 4100K 5000K | 36" | 240° | UL | 5-Years |
| LBT8F16xxB | Plug-n-Play | G13 | 13W / 32W | 1650 lm | 3500K 4100K 5000K | 48" | 240° | UL | 5-Years |
| LBT8F18xxB | Plug-n-Play | G13 | 15W / 32W | 1800 lm | 3500K 4100K 5000K | 48" | 240° | UL | 5-Years |
| LBT8F22xxB | Plug-n-Play | G13 | 19W / 32W | 2200 lm | 3500K 4100K 5000K | 48" | 240° | UL | 5-Years |

NOTE 1: Please reference our Ballast Compatibility List.

NOTE 2: Replace xx with 35 for 3500K, 41 for 4100K, and 50 for 5000K Color Temperature

NOTE 3: Savings calculated by 50,000 hour Lifetime, Electricity rated \$0.12, and 3 Operating Hours Per Day.





