



LED PL RETROFIT LAMPS
PL DirectFit Series




PRODUCT DESCRIPTION:

MaxLite LED PL DirectFit lamp is the ideal plug and play solution that works straight out of the box. The 13W LED PL lamp is designed to replace CFL downlights with 4-pin G24q sockets. These energy-saving LED lamps are quick, easy and safe to install into existing CFL fixtures without any extra effort or re-wiring. Available in horizontal and vertical installation position and 3 different correlated color temperature.

FEATURES:

- Input Power: 13W
- Input Voltage: determined by CFL ballast
- Color Rendering Index (CRI): ≥80
- 50,000 Hour life
- High power factor: ≥.90
- Rotatable 270° (Horizontal model)
- Compatible with most electronic CFL ballasts
- Instant on
- Suitable for use with wall-mounted and ceiling fixtures
- Suitable for damp locations
- Five year limited warranty

APPLICATIONS:



MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: 13PLG24QHLED27		
13	PL	G24Q		
WATTAGE	FAMILY	BASE	INSTALLATION POSITION	COLOR TEMPERATURE (CCT)
13= 13 watts	PL	G24Q= G24q 4-pin	HLED= Horizontal VLED= Vertical	27= 2700K 35= 3500K 41= 4100K

NOTES:

1. ENERGY STAR and DLC does not currently have a category for this product type.

SPECIFICATIONS:

ITEM	SPECIFICATION	13W HORIZONTAL			13W VERTICAL		
		DETAILS			DETAILS		
GENERAL PERFORMANCE	Color Temperature	2700K	3500K	4100K	2700K	3500K	4100K
	Lumens Delivered (lm)	850	900		850	900	
	Efficacy (lm/w)	65	69		65	69	
	Lumen Maintenance (L70)	50,000 hours			50,000 hours		
ELECTRICAL	Power Factor	≥.90			≥.90		
	Input Voltage	Dependent on CFL electronic ballast			Dependent on CFL electronic ballast		
PHYSICAL	Operating Temperature	-4° F to 105° F			-4° F to 105° F		
APPLICATION	Environment	Damp			Damp		
	Warranty	5 Year			5 Year		

ORDERING*:

ORDER CODE	WATTAGE	MODEL	CCT	OUTPUT (LUMENS)	EQUIVALENCY	DIMENSIONS (L" x W")
13W HORIZONTAL						
74862	13	13PLG24QHLED27	2700K	850	26W (32W & 42W)	5.22" x 1.62"
74863	13	13PLG24QHLED35	3500K	900		
74864	13	13PLG24QHLED41	4100K	900		
13W VERTICAL						
74865	13	13PLG24QVLED27	2700K	850	26W (32W & 42W)	4.66" x 2.14"
74866	13	13PLG24QVLED35	3500K	900		
74867	13	13PLG24QVLED41	4100K	900		

*Please contact your MaxLite representative to order products that don't have order codes listed here.

COMPATIBLE BALLASTS:

MANUFACTURER	MODEL
ADVANCE	ICF-2S13-M1-BS
ANTRON	CSS-UV42PS/C6YO
ANTRON	CSS-UV42PS/C6YM
ANTRON	CSD-UV18PS/C6YO
HALCO	EP2CF26PS/MV/DC/K
HOWARD	EP2/26CF/MV/2
STANDARD	31278STD
STANDARD	31276STD
SYLVANIA	QTP2X26CF/UNV DM
TOSPO	TP-2/26PS UV
UNIVERSAL TRIAD	C2642UNVME