

DESCRIPTION

CATALOG: E-750-U-260	BALLAST TYPE: Electronic	STARTING METHOD: Instant Start	NUMBER OF LAMPS – LAMP TYPE: 1 - F96T12, 2 - F96T12
-------------------------	-----------------------------	-----------------------------------	--

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE: 120 - 277 V~ ± 10%	LAMP WATTS: 60/75 w	INPUT WATTS: 134 w	INPUT CURRENT: 1.12/0.5 A	OCV: 660 v	PF: > 0.97	FREQUENCY: 50/60 Hz	SOUND RATED: A
MIN START TEMP: 32°F / 0°C	CLASS: P	TYPE: 1 outdoor	BALLAST FACTOR: 0.86	BEF: 0.64	LAMP CONNECTION: PARALLEL	THD (1): < 19%	NO PCB'S

(1) FOR 2-F96T12

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	UNITS	M1	M2	M3	W	L	H
	INCHES	2.0	11.14	10.5	3.11	11.75	1.78
	TOL(+/-)	0.01	0.03	0.01	0.05	0.10	0.08
	MM	51	283	267	79	298	45
	TOL(+/-)	0.25	0.8	0.25	1.30	2.50	2.00
	LEAD LENGTH						
UNITS	BLACK	WHITE	RED	BLUE	BLUE		
INCHES	22	22	57	47	47		
TOL(+/-)	3/8	3/8	3/8	3/8	3/8		
MM	559	559	1448	1194	1194		
TOL(+/-)	10	10	10	10	10		

CARTON CHARACTERISTICS


UNITS/CARTON 6	CARTONS/LAYER 12	# OF LAYERS 8	UNITS/PALLET 576	PIECE WEIGHT 3.74 lbs	CARTON WEIGHT 23 lbs	PALLET WEIGHT 2,285 lbs
CARTON / PALLET 96	CARTON DIMENSIONS 12" x 12" x 4"	PALLET DIMENSIONS 40" x 48" x 7"	PALLET DIMENSIONS LOADED INCLUDING WOOD PALLET 40" x 48" x 40"			

MISC.

--

CARTON LABEL

ELECTRICAL DIAGRAM



PRODUCT LABEL



ISO 9001:2000



Data is based upon test performed by Industrias Sola Basic in a controlled environment and representatives of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

Made in Mexico by Industrias Sola Basic S.A. de C.V.