Modern A19 Lamp Series

For today's general lighting, choose Halco's Modern A19 Rough Service and Vibration Service lamps.

Halco's Modern A19 Incandescent lamps feature both Rough Service and Vibration Service lamps, providing long life in not so ideal conditions. Unlike standard Incandescent lamps, Modern A19 Incandescent lamps feature filaments that utilize multiple supports to provide stability. The extra supports help prevent the filament from breaking prematurely in applications where the lamps are susceptible to bumps, vibrations or movement. Both versions also feature a brass rather than an aluminum base, to help withstand corrosion. With the Modern A19 Series you can enjoy the longer life without losing the warm feel of a standard Incandescent lamp.

Rough Service

Rough Service lamps feature a C7-A filament which utilizes 7 supports to prevent movement and provide 3000 hour lamp life at 130V. Rough Service lamps are available in 40W, 60W, 75W and 100W with either a Frost or Clear finish and are exempt from Incandescent legislation.

Vibration Service

Vibration Service lamps feature a C-9 filament which utilizes 5 supports to prevent movement and provide 2500 hour lamp life at 130V compared to 1500 hour standard A19s. Vibration Service lamps are available in 40W and 60W with either a Frost or Clear finish and are exempt from Incandescent legislation.

| | | Rough Service A19 | | | Vibration Service A19 | | | |
|---------|-----------|-------------------|------------|----------------------|-----------------------|------------|----------------------|--|
| Wattage | Base Type | Life@ 130V | Life@ 120V | Filament Supports | Life@ 130V | Life@ 120V | Filament Supports | |
| 40 | Brass | 3000 hours | 8550 hours | 7 | 2500 hours | 7125 hours | 5 | |
| 60 | Brass | 3000 hours | 8550 hours | 7 | 2500 hours | 7125 hours | 5 | |
| 75 | Brass | 3000 hours | 8550 hours | 7 | | | | |
| 100 | Brass | 3000 hours | 8550 hours | 7 | | | | |



Modern A19 Lamp Series

Ordering Information

| Watt | Base | Product # | Product Code | Description | Volts | Filament Design | Lumens | Avg. Rated Life (130V) | Pkg. Qty. | MOL |
|---------------|-------------------|-----------|--------------|-------------|-------|--------------------|--------|------------------------------|--------------|-------|
| Rough Service | | | | | | | | | | |
| 40 | E26 | 76008 | A19CL40/RS | Clear | 130 | C-7A | 280 | 3000 | 4/120 | 4.25" |
| 40 | E26 | 76009 | A19FR40/RS | Frosted | 130 | C-7A | 270 | 3000 | 4/120 | 4.25" |
| 60 | E26 | 76010 | A19CL60/RS | Clear | 130 | C-7A | 515 | 3000 | 4/120 | 4.25" |
| 60 | E26 | 76011 | A19FR60/RS | Frosted | 130 | C-7A | 500 | 3000 | 4/120 | 4.25" |
| 75 | E26 | 76012 | A19CL75/RS | Clear | 130 | C-7A | 700 | 3000 | 4/120 | 4.25" |
| 75 | E26 | 76013 | A19FR75/RS | Frosted | 130 | C-7A | 680 | 3000 | 4/120 | 4.25" |
| 100 | E26 | 76014 | A19CL100/RS | Clear | 130 | C-7A | 1050 | 3000 | 4/120 | 4.25" |
| 100 | E26 | 76015 | A19FR100/RS | Frosted | 130 | C-7A | 1000 | 3000 | 4/120 | 4.25" |
| Vibration | Vibration Service | | | | | | | | | |
| 40 | E26 | 76016 | A19CL40/VS | Clear | 130 | C-9 | 320 | 2500 | 2/120 | 4.25" |
| 40 | E26 | 76017 | A19FR40/VS | Frosted | 130 | C-9 | 310 | 2500 | 2/120 | 4.25" |
| 60 | E26 | 76018 | A19CL60/VS | Clear | 130 | C-9 | 660 | 2500 | 2/120 | 4.25" |
| 60 | E26 | 76019 | A19FR60/VS | Frosted | 130 | C-9 | 640 | 2500 | 2/120 | 4.25" |

EISA 2007 legislation allows an exemption for vibration service incandescent lamps to be sold with a maximum of 60W.