

SOLUX HALOGEN LAMPS

Exclusive True Daylight MR16 & PAR



- **True Daylight, 24/7**
The only lighting technology able to replicate daylight and render products' colors the way they naturally appear
- **High CRI**
More accurately reproduces color
- **Ideal for Color Sensitive Applications**
Decrease product returns based on inaccurate color reproduction. Enhance the appeal of art, photography and jewelry
- **Low IR/UV Emission**
Will not cause fading over time from IR or UV lighting exposure



Selection. Solutions. Simplicity.

23220 W. 84th St., Shawnee, KS 66227 • Ph: 1.800.852.2217 • Fax: 1.913.441.6679 • Email: eiko@eiko.com
EiKO CANADA: 31 King St. Unit 7, Barrie, Ontario L4N 6B5, Canada • Ph: 1.705.721.5189 • Fax: 1.705.721.7855

www.eiko.com

SoLux MR16 3500K Lamps
 35 & 50 Watt * 12 Volt * 10°-36° Beam Angle

Ordering Code	Watts	Volts	Base	Filament	MOL	MOD	Life Hours	CRI	Beam Angle
18006	50	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	10
18007	50	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	17
18008	50	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	36
18009	50	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	24
35006	35	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	10
35007	35	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	17
35008	35	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	36
35009	35	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	24

SoLux MR16 4100K Lamps
 35 & 50 Watt * 12 Volt * 10°-36° Beam Angle

Ordering Code	Watts	Volts	Base	Filament	MOL	MOD	Life Hours	CRI	Beam Angle
18011	50	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	10
18012	50	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	17
18013	50	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	36
18014	50	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	24
35011	35	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	10
35012	35	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	17
35013	35	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	36
35014	35	12	GU5.3	C-8	1.77/45	1.97/50	4000	98+	24

SoLux MR16 4700K Lamps
 35 & 50 Watt * 12 Volt * 10°-36° Beam Angle

Ordering Code	Watts	Volts	Base	Filament	MOL	MOD	Life Hours	CRI	Beam Angle
18001	50	12	GU5.3	C-8	1.77/45	1.97/50	4000	99+	10
18002	50	12	GU5.3	C-8	1.77/45	1.97/50	4000	99+	17
18003	50	12	GU5.3	C-8	1.77/45	1.97/50	4000	99+	36
18004	50	12	GU5.3	C-8	1.77/45	1.97/50	4000	99+	24
35001	35	12	GU5.3	C-8	1.77/45	1.97/50	4000	99+	10
35002	35	12	GU5.3	C-8	1.77/45	1.97/50	4000	99+	17
35003	35	12	GU5.3	C-8	1.77/45	1.97/50	4000	99+	36
35004	35	12	GU5.3	C-8	1.77/45	1.97/50	4000	99+	24

SoLux PAR 3500K Lamps
 PAR20, PAR30 & PAR38 * 50, 75 & 90 Watt * 10, 30 & 50 Deg Beam Angle

Ordering Code	Watts	Volts	Shape	Base	Lumens	Life Hours	CRI	Beam Angle
50PAR20/FL30/3500K	50	120	PAR20	Medium Screw (E26)	275	2500	90	30
50PAR20/SP10/3500K	50	120	PAR20	Medium Screw (E26)	275	2500	90	10
75PAR30/FL30/3500K	75	120	PAR30	Medium Screw (E26)	600	2500	90	30
75PAR30/SP10/3500K	75	120	PAR30	Medium Screw (E26)	600	2500	90	10
90PAR38/FL30/3500K	90	120	PAR38	Medium Screw (E26)	800	2500	90	30
90PAR38/SP10/3500K	90	120	PAR38	Medium Screw (E26)	800	2500	90	10
90PAR38/WFL50/3500K	90	120	PAR38	Medium Screw (E26)	800	2500	90	50

NOTES:

SOLUX LAMPS

Appendix A – Charts

