

ProLED_a A19 and BR30 Contractor Series 6 Pack







The Halco Contractor Series 6 Pack gives you a performance product at an economical price







15,000 Hours Useful Life

Acceptable for use in insulated contact airtight (ICAT) rated fixtures

Backed by a 3-Year Warranty

Applications:

A19:

Retail

Hospitality

Residential

BR30:

Residential

Light Commercial

Hospitality

Markets:

Residential


Commercial




ProLED. **A19 Contractor Series 6 Pack**

Specifications

- 15,000 hour life resulting in lower maintenance costs over time
- 88 lumens per watt
- 82 CRI for quality and consistent color rendering
- UL approved for damp locations
- ICAT rated
- Omnidirectional
- Non Dimmable



Savings Comparison



V Maintenance costs based on 15 minutes at \$40 per/hr

Savings Comparison

¥ Energy costs based on \$0.11 kWh

A19 Ordering Information

	Watt§	Base	Product #	Product Code	Volts†	Color Temp.	CRI	Lumens	Useful Life*	Beam Spread	Pkg. Qty.	MOL	Equivalent Wattage
0	9	Medium	82069	A19FR9/830/ECO/LED/6	120	3000K	82	800	15,000	240°	6/24	4.29"	60


[•] NEW ITEM

ProLED.


BR30 Contractor Series 6 Pack

Specifications

- 15,000 hour life resulting in lower maintenance costs over time
- 82 lumens per watt
- 82 CRI for quality and consistent color rendering
- UL approved for damp locations
- ICAT rated
- Dimmable



Total Lifetime Costs \$120



V Maintenance costs based on 15 minutes at \$40 per/hr ¥ Energy costs based on \$0.11 kWh

BR30 Ordering Information

	Watt [§]	Base	Product #	Product Code	Volts†	Color Temp.	CRI	Lumens	Useful Life*	Beam Spread	Pkg. Qty.	MOL	Equivalent Wattage
0	9	Medium	82070	BR30FL9/830/ECO/LED/6	120	3000K	82	650	15,000	110°	6/24	5.1"	65

Useful Life is defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to burn past this point, but at decreased light levels. Warranty - Commercial / Industrial: This product is warranted for 3 years from the date of purchase, based on 10 hours of use per day. Must be operated with an ambient fixture temperature between -4°F(-20°C) and 122°F(50°C).

Useful Life is defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to burn past this point, but at decreased light levels Warranty - Commercial / Industrial: This product is warranted for 3 years from the date of purchase. Must be operated with an ambient fixture temperature between -4°F(-20°C) and 122°F(50°C).