



duct Family Name: I n Number: dering Code:	Filaments: Fully Compatible E 77665(LED4B11/27K/FIL/E12/2	6 776	5659 776660 12/2 LED4CA10/27K/FIL/E12/F/2					
tem Number: Drdering Code:	776664 LED4CA10/30K/FIL/E12/2		5672 776673 /F/2 LED4G16/27K/FIL/E12/2					
	Manufacturer	Product	Model Number	Overall Rating	Lamps per Recommended Minimum	Dimmer Maximum Tested*	Notes	
_	L an it and	IllumaTech	IPI06	Good	1	6	Minor flicker at Medium with 1, 2+ best dims down to 1%	
	Leviton	SureSlide Vizia	6633-P VPI06-1LZ	Good Good	1	6	Minor flicker at Medium with 1, 2+ best dims down to 1% Minor flicker at Medium with 1, 2+ best dims down to 1%	
		Toggler	TG-600	Good	1	6	Shimmer at Med with 1, 2 + best dims down to 1%	
candescent/Halogen (Triac/Phase	Lutron	Diva	DV-600	Good	1	6	Shimmer at Med with 1, 2+ best dims down to 1%	
Cut/Leading Edge Dimmers)		Skylark Maestro	S-600 MAW-600	Good Bad	1	6	Shimmer at Med with 1 , 2+ best dims down to 1% 4+ minimum load	
	Legrand	Titan	CD703-PW	Bad	1	6	Flicker at Med 1& at LE 2-4 , 5+ best , dims down to 1%	
		Titan	CDLV703-PW	Good	1	6	Minor flicker at Med 1-2 , 3+ best , dims down to 1%	
		Harmony	D703-PTC	Bad	1	6	Flicker at Med to HE 1-2, 3+ best, dims down to 1%	
		Harmony	H703-PTC	Good	1	6	Flicker at Med to HE 1 , 2+ best , dims down to 1%	
-		IllumaTech	IPL06	Best	1	6	Dims down to 1%	
	Leviton	Sureslide	6674	Best	1	6	Dims down to 1%	
		Decora Diva	6672	Best	1	6	Dims down to 1%	
		Diva Toggler	DVCL-153PL TGCL-153PH	Good Good	1	6	Minor flicker 1-2 , 3+ best , dims down to 1% Minor flicker 1-2 , 3+ best , dims down to 1%	
CFL/LED	Lutron	Maestro	MACL-153MLH	Best	1	6	Dims down to 1%	
	LUCION	Skylark	CTCL-153	Good	1	6	Minor flicker 1-2, 3+ best, dims down to 1%	
-		Skylark Radio RA	SCL-153P RA2RR-6CL-PD	Best Best	1	6	Dims down to 1% Dims down to 1%	
		Harmony	DCL453-PTC	Good	1	6	Minor flicker 1-2 , 3+ best , dims down to 1%	
	Legrand	Harmony	HCL453PTC	Good	1	6	Minor flicker 1-2 , 3+ best , dims down to 1%	
		Adorne Paddle	ADPD453LM2	Best	1	6	Dims down to 5%	
		Vizia	VPE04	Best	1	б	Dims down to 1%	
Electronic Low Voltage	Leviton	IllumaTech	IPE04	Good	1	6	Minor flicker at Med 1 , minor flicker at LE 1-6 , dims down 1%	
		Decora	6615-P	Good	1	6	Minor flicker at LE & Med 1-6 , dims down 15%	
		Skylark	SELVB-300P	Good	1	6	Shimmer at Med 1-6, dims down to 1%	
		Skylark Countour Diva	CTELV-303P DVELV-300P	Good Good	1	6	Shimmer at Med 1-4 , dims down to 1 % Shimmer at Med 1-2 ,dims down to 1%	
		Maestro	MAELV-600	Best	1	6	Dims down to 1%	
		VIERTI	VTEL-600M-W	Best	1	6	Dims down to 1%	
	Legrand	Scene Director	SCELV	Good	1	6	Shimmer at LE 1-6 , dims down to 1%	
Magentic Low Voltage	Louiton	Vizia	VPM-06	Good	1	6	Minor flicker at LE- Med 1-2 , 3+ best , dims down to 1%	
	Leviton	Decora	6613-P	Good	1	6	Minor flicker at Med 1-2 , 3+ best , dims down to 1%	
	Lutron	Maestro	MALV-600 DLV703-PW	Bad Good	1	6	6+ minimum load, dims down to 5%	
	Legrand	Harmony	DLV703-PVV	Good	L	0	Minor flicker at Med 1, 2+ best , dims down to 1%	
Universal		Adorne SofTap	ADTP703TU	Good	1	6	Shimmer at LE 1-6 , dims down to 5%	
		Miro Decorator	DRD4-W	Bad	1	6	Flicker at LE 1-6, dims down to 10%	
	Legrand	Harmony Adorne Whisper	H703PTUTC ADWR700MMTUW2	Good Good	1	6	Shimmer at LE 1-6 , dims down to 15% Shimmer at LE 1-6 , dims down to 1%	
		Adorne Touch	ADTH700MMTUM2	Good	1	6	Shimmer at LE 1-6 , dims down to 1%	
	Cooper	Decorator	DAL06P-C2-K-L	Good	1	6	Minor flicker at LE 1-6 , dims down to 5%	
Maximum Tested (Lamps per Dimmer) - A May experience "pop-on", lights cannot be ere initially off. Then, the slider can be lov	dditional lamps may work with e turned on immediately to thei	ir minimum level. The slider n	needs to be raised above the minimum l		1 rn on if they	6	Minor flicker at LE 1-6 , dims down to 5%	
verall Rating	One or more of the following	obsorved: Major flickering	a at various points, significant audih	la noisa, na dimming ranga, a	and not turn off			
	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off. One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.							
(One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These							
	periods of dead travel are minor and most of the time not visible. Minor audible noise.							
pod	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output.							
DOD	8	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.						