


TRACK 33W L HIGH CRI

Preliminary Specifications



DIMENSIONS



PRO



- ⌚ Exceptional color rendering CRI 90+
- ⌚ 2300 lumen output replaces 39W HID
- ⌚ Field interchangeable lens comes in NF & FL standard
- ⌚ Sleek design, integrated driver
- ⌚ Tight binning: 3-step Macadam ellipse




40,000 H



DIMMABLE



EFFICACY



WARRANTY



CRI (Ra)



DIRECTIONAL



COMPATIBLE WITH H, J & L TRACK TYPE



TRACK 33W L HIGH CRI

Preliminary Specifications

SPECIFICATIONS*

Product	33TRLG4DIM/927/_/_	33TRLG4DIM/930/_/_	33TRLG4DIM/940/_/_ (MTO)
Track Type	H/J/L (L-MTO)	H/J/L (L-MTO)	H/J/L (L-MTO)
Power (W)	33.8	33.8	33.8
Voltage - Frequency	120V 60Hz	120V 60Hz	120V 60Hz
Color Temp. (ANSI)	Warm White 2700K	Warm White 3000K	Natural White 4000K
CRI (Ra) (typ.)	90	90	90
Typical lumens (lm)	2200	2300	2400
Efficacy (LPW)	65	68	71
Beam Angle	NF 25° / FL 38°	NF 25° / FL 38°	NF 25° / FL 38°
CBCP (cd)	10,000 / 5150	10,350 / 5250	11,000 / 5650
Dimmable	Yes	Yes	Yes
Power Factor	0.9	0.9	0.9
Rated Lifetime - L70 (hrs.)	40,000	40,000	40,000
H x L x Dia.	6.69"x5.90"x3.54" (170x150x90mm)	6.69"x5.90"x3.54" (170x150x90mm)	6.69"x5.90"x3.54" (170x150x90mm)
Weight (lb. / g)	1.31lb / 595g	1.31lb / 595g	1.31lb / 595g
Finish	White / Black	White / Black	White / Black

ORDERING INFORMATION

Model	Finish	Track Type
33TRLG4DIM/927/	W-White	H-Halo
	B-Black	J-Juno
		L-Lightolier

Example: 33TRLG4DIM/927/W/J

Note: Every product comes standard with NF 25° mounted lens and FL 38° accessory lens.

* Specification data is preliminary and may be subject to change