S9394

54W/LED/HID/5000K/100-277V
54 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

S9394

Features
- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- DLC Qualified
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C

Additional Technical Specifications
- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V

Minimum Compartment Size		
Length	Width	Depth
17.3 inch	9.25 inch	9.25 inch

Optional accessory: In-line surge protector 80-929

Item Number	Product Line	UPC	Input Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S9394	Hi-Pro	045923093944	100 - 277	54	300W	85W	250W

Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Mogul Extended	EX39	54W/LED/HID/5000K/100-277V	Non-Dimmable	White	10-3/4"	3.69"	7200

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type

50000	5000	Stark White	80+	300	-20C (-4F) to a maximum of +65C (+149F)	12	Box

DLC ID:	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
P7RMM9YA; PMM9NX2Z DLC Search	Yes	Yes	cULus - Damp Location Rated	5 Year Limited