



GE
Lighting

68922 - F32T8/SPX41/U6/2

F32T8/SPX41/U6/2

Product Photo



GENERAL CHARACTERISTICS

| | |
|---------------------------------|--------------------|
| Base Description | Medium Bi-Pin |
| Base Type | Pin/Plug-In |
| Mercury Content | 90 mg |
| Mercury-Picogram per mean lm hr | 1711 |
| Rated Life Rapid Start - Hrs | 20000 h @ 3 h |
| Starting Temp (MIN) C-degrees | 10 °C |
| Bulb Material | Sodalime glass |
| Rated Life Hours-nominal | 20000 h |
| Primary Application | Full Wattage |
| Product Technology | Linear Fluorescent |
| Base | G13 |
| Bulb Shape | T8 |

PHOTOMETRIC CHARACTERISTICS

| | |
|--------------------------------|---------|
| Mean Lumens nominal | 2465 lm |
| Nominal Initial Lumen per Watt | 88 |
| Initial Lumens-nominal | 2800 lm |
| Color Rendering Index-CRI | 82 |
| Color Temperature | 4100 K |

PRODUCT INFORMATION

| | |
|----------------------------------|------------------|
| Product Code | 68922 |
| Description | F32T8/SPX41/U6/2 |
| Alternative Unit Of Measure | CASE |
| Standard Package Quantity | |
| Ean UPC | 043168689229 |
| Standard Package GTIN | 10043168689226 |
| No Of Items Per Sales Unit | |
| No Of Items Per Standard Package | |
| Sales Unit | Case |
| UCC | 043168689229 |

DIMENSIONS

| | |
|----------------|---------|
| Diameter | 1.0 in |
| Nominal Length | 22.5 in |

ELECTRICAL CHARACTERISTICS

| | |
|---------------------|------|
| Rated power (Watts) | 32 W |
|---------------------|------|