PL H 6W BYP TITANIUM LED SERIES











- (1) HYBrid installation DIRect or BYPass
- Compatible with magnetic ballasts DIRect installation
- Built-in universal voltage driver Bypass installation
- Compatible with G24d, GX24d, G24g & GX24g bases
- Exceptional efficacy 93 LPW
- U Lasts 4 times longer than CFL



























PL PRODUCT FEATURES

BYPass Installation - Electronic Ballasts

This PL H lamp is not compatible with electronic ballasts and requires bypassing the ballast during installation. The lamp runs directly off line voltage to eliminate compatibility problems, incidental power loss, lifetime issues, and maintenance costs associated with ballasts.




HYBrid Installation - DIRect or BYPass - Magnetic Ballasts





When used with a magnetic ballast, the PL H can function as a plug & play lamp and operate with the existing ballast. If the ballast is not compatible, it can be bypassed and the lamp can run directly off line voltage.

PL H 6W BYP TITANIUM LED SERIES










Base: G24d, GX24d, G24q & GX24q (2/4-pin CFL)

Voltage: Magnetic ballast compatible

120-277V

Dimmable: No PF: 0.9

Lifetime (L70): 50,000 hrs
Weight: 0.15lb / 68g



SPECIFICATIONS

Model	Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
6PLH/835/BYP/R	57904	6	Halogen White 3500K	82	550	92	(110°)
6PLH/840/BYP/R	57905	6	Cool White 4000K	82	560	93	110°

^{*} Suitable for damp locations. Not for use where directly exposed to weather or water

** Not intended for use in enclosed fixtures

^{***} Full installation guide and more details available on website